



Features:

- Positioning within
- <p>EUROLITE LED KLS Scan Next FX Compact Light Set
- **Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag**
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- When fog is used, this effect becomes especially attractive
- Positioning within
- Color wheel; gobo wheel with static gobos
- Color wheel with 8 dichroic filters plus open
half colors selectable
- 20 integrated show programs
- Can be operated in 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 CH mode
- The device is cooled by cooling fan
- Control via DMX; IR remote control; sound to light via microphone; stand-alone; master/slave function; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- TV spigot
- With mounting bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand
- **spotlight**
- 3 LEDs 7 W high-power 4in1 RGB/WW (homogenous color mix)
4 spots controlled separately
- With a beam angle of 15°
- **light effect**

Logistic

EAN / GTIN: 4026397690842

Weight: 14,80 kg

Length: 1.30 m

Width: 0.50 m

Height: 0.30 m

Bulky product

- 2 LEDs 3 W R/G/B
moving light
- 1 LED 15 W cold white (CW)
bar
- 4 LEDs 1 W high-power ultra violet (UV)
 LEDs controlled separately
- <p>EUROLITE Foot Switch KLS Compact Light Set MK2
Wireless foot switch for KLS Compact Light Sets
- Powered by a battery/battery pack
- The device is cooled by passive convection cooling
- Operating range up to 30m with line-of-sight
- The article is delivered ready to stand
- Non-slip pedal housing

Technical specifications:

Weight:	13.49 kg
---------	----------

EUROLITE LED KLS Scan Next FX Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	115 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
Equipment:	Color wheel; gobo wheel with static gobos
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; IR remote control; sound to light via microphone; stand-alone; master/slave function; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x mounting bracket
Display type:	OLED display
Dimensions:	Width: 110 cm Depth: 15.5 cm Height: 43 cm
Weight:	12.80 kg

Noise classification:	Class 3 (clearly perceptible sounds)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	4 x 1 W high-power ultra violet (UV)
LED type:	2 x 3 W R/G/B
LED type:	3 x 7 W high-power 4in1 RGB/WW (homogenous color mix)
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	28°
Illuminance in Lux (lx):	Red (R) 1m: 1022 lx, 3m: 125 lx, 6m: 33 lx Green (G) 1m: 2448 lx, 3m: 285 lx, 6m: 75 lx Blue (B) 1m: 395 lx, 3m: 47 lx, 6m: 13 lx Warm white (WW) 1m: 1892 lx, 3m: 219 lx, 6m: 58 lx All 1m: 4853 lx, 3m: 676 lx, 6m: 175 lx
LED type:	1 x 15 W cold white (CW)

EUROLITE Foot Switch KLS Compact Light Set MK2

Protection class:	Protection class III
Power connection:	Battery/battery pack built-in
Battery:	1 x 9.0 V E block 6F22 zinc carbon built-in
Cooling:	Passive convection cooling
Range:	Range up to 30m with line-of-sight
Carrier frequency:	433.92 MHz
Housing color:	Black matte
Material:	Plastic hard
Housing design:	Non-slip pedal housing
Dimensions:	Width: 42.0 cm Depth: 14.0 cm Height: 4.5 cm
Weight:	0.69 kg

Scope of delivery:

1 x EUROLITE LED KLS Scan Next FX Compact Light Set

1 x device
 1 x user manual
 1 x power cord
 1 x declaration of conformity
 2 x mounting bracket
 1 x remote control
 1 x battery
 1 x bag
 2 x knurled screw
 2 x washer
 1 x terminating plug (power)

1 x EUROLITE Foot Switch KLS Compact Light Set MK2

1 x foot control
 1 x declaration of conformity
 1 x battery