



The article is no longer in our assortment.

Features:

- Positioning within
- <p>EUROLITE LED KLS Scan Next FX Compact Light Set
- **Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag**
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- When fog is used, this effect becomes especially attractive
- Positioning within
- Color wheel; gobo wheel with static gobos
- Color wheel with 8 dichroic filters plus open
half colors selectable
- 20 integrated show programs
- Can be operated in 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 CH mode
- The device is cooled by cooling fan
- Control via DMX; IR remote control; sound to light via microphone; stand-alone; master/slave function; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- TV spigot
- With mounting bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand
- **spotlight**
- 3 LEDs 7 W high-power 4in1 RGB/WW (homogenous color mix)
4 spots controlled separately
- With a beam angle of 15°
- **light effect**

Logistic

EAN / GTIN: 4026397690859
 Weight: 23,22 kg
 Length: 1.20 m
 Width: 0.80 m
 Height: 1.35 m
 Bulky product

- 2 LEDs 3 W R/G/B
moving light
- 1 LED 15 W cold white (CW)
bar
- 4 LEDs 1 W high-power ultra violet (UV)
 LEDs controlled separately
- <p>EUROLITE QuickDMX USB Wireless Transmitter/Receiver
Wireless miniature DMX transceiver 2.4 GHz, phantom powered
- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference
- <p>EUROLITE QuickDMX Wireless Transmitter
Compact wireless DMX transmitter 2.4 GHz
- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference
- <p>EUROLITE DMX LED Color Chief Controller
DMX lighting desk with innovative control concept for LED spotlights
- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- <p>EUROLITE STV-60-WOT EU Steel Stand black
Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm
- Stable lighting stand for mobile use
- Adjustable height
- TV spigot
- Available in various colors
- Made in Europe

Technical specifications:

Weight:	20.86 kg
---------	----------

EUROLITE LED KLS Scan Next FX Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	115 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
Equipment:	Color wheel; gobo wheel with static gobos
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; IR remote control; sound to light via microphone; stand-alone; master/slave function; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x mounting bracket
Display type:	OLED display
Dimensions:	Width: 110 cm Depth: 15.5 cm Height: 43 cm
Weight:	12.80 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	4 x 1 W high-power ultra violet (UV)
LED type:	2 x 3 W R/G/B
LED type:	3 x 7 W high-power 4in1 RGB/WW (homogenous color mix)
Beam angle:	15°

Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	28°
Illuminance in Lux (lx):	Red (R) 1m: 1022 lx, 3m: 125 lx, 6m: 33 lx Green (G) 1m: 2448 lx, 3m: 285 lx, 6m: 75 lx Blue (B) 1m: 395 lx, 3m: 47 lx, 6m: 13 lx Warm white (WW) 1m: 1892 lx, 3m: 219 lx, 6m: 58 lx All 1m: 4853 lx, 3m: 676 lx, 6m: 175 lx
LED type:	1 x 15 W cold white (CW)

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
Protection class:	Protection class III
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Housing color:	Black
USB port:	Type A
Material:	Plastic
Color:	Black
Dimensions:	Width: 8.6 cm Depth: 4 cm Height: 1.1 cm
Weight:	0.01 kg

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm

Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21.2 cm Diameter: Ø 1.8 cm
Weight:	0.15 kg

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA
Power consumption:	7.2 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Programmable 24 scenes/chases distributed over 1 page/s
DMX channels:	Output 240
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone
Housing color:	Black
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 13.35 cm Height: 8.5 cm
Weight:	2.25 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE STV-60-WOT EU Steel Stand black

Maximum carrying capacity:	30 kg
Height:	Maximum: 320 cm Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Material:	Steel/magnesium
Color:	Black
Transport dimensions:	126 cm x 12 cm x 15 cm
Weight:	5.65 kg

Scope of delivery:

1 x EUROLITE LED KLS Scan Next FX Compact Light Set

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x declaration of conformity
- 2 x mounting bracket
- 1 x remote control
- 1 x battery
- 1 x bag
- 2 x knurled screw
- 2 x washer
- 1 x terminating plug (power)

1 x EUROLITE QuickDMX USB Wireless Transmitter/Receiver

- 1 x device
- 1 x user manual
- 1 x declaration of conformity

1 x EUROLITE QuickDMX Wireless Transmitter

- 1 x device
- 1 x user manual
- 1 x declaration of conformity
- 1 x external mains adapter
- 1 x USB cable

1 x EUROLITE DMX LED Color Chief Controller

- 1 x controller
- 1 x user manual
- 1 x external mains adapter

1 x EUROLITE STV-60-WOT EU Steel Stand black

- 1 x stand
- 1 x user manual