



The article is no longer in our assortment.

Features:

EUROLITE AKKU IP Flat Light 3 bk

Flat IP65 spotlight in black with 3 x 8 W 4in1 RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color change adjustable; colors preset
- Strobe effect
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 15°
- With mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels

Logistic

EAN / GTIN: 4026397691047

Weight: 13,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Silent operation
- Application possibility: Standing

EUROLITE Charger 4x Akku Flat Light Series

Power supply with cable for simultaneous charging of 4 x AKKU Flat Light 1/3

ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	11.08 kg
---------	----------

EUROLITE AKKU IP Flat Light 3 bk

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery/battery pack
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	3 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
Fixtures available for:	Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz

Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Width: 17.2 cm Depth: 13.8 cm Height: 6.2 cm
Weight:	1.61 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

EUROLITE Charger 4x Akku Flat Light Series

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 6000 mA
Power connection:	Mains input via C8 (M) "figure 8" mounting version power supply cord with Euro plug (provided)
Power output:	4 x coaxial power connector (F)
Weight:	0.49 kg

ROADINGER Flightcase 4x AKKU Flat Light Series

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	8 cm x 19 cm x 10 cm
Accessory compartment:	38 cm x 6.5 cm x 12 cm
Inside dimensions:	38 cm x 27 cm x 12 cm
Dimensions:	Width: 42 cm Depth: 31 cm Height: 20 cm
Weight:	4.15 kg

Scope of delivery:

4 x EUROLITE AKKU IP Flat Light 3 bk

- 1 x device
- 1 x external mains adapter
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x declaration of conformity
- 1 x user manual

1 x EUROLITE Charger 4x Akku Flat Light Series

- 1 x charger
- 1 x power cord
- 1 x adapter cable