



### Features:

#### EUROLITE LED IP PAR 7x8W QCL Spot

Weather-proof (IP65) spotlight with 7 x 8 W LED and 4in1 RGBW color mixing

- 7 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 3; 4; 5; 6; 10 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397694178

Weight: 38,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

## ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Trunk case with castors, PRO version

- With 4 device compartments
- With 1 accessory compartment
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 34.03 kg |
|---------|----------|

### EUROLITE LED IP PAR 7x8W QCL Spot

|                         |                                                                                                                                                                       |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                |
| Power consumption:      | 55 W                                                                                                                                                                  |
| IP classification:      | IP65                                                                                                                                                                  |
| Power connection:       | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug                                                                                   |
| Power output:           | IP T-Con (F) mounting version                                                                                                                                         |
| Lamp type:              | LED lamp                                                                                                                                                              |
| LED type:               | 7 x 8 W high-power 4in1 RGBW (homogenous<br>color mix)                                                                                                                |
| Flash rate:             | 0.5 - 24 Hz                                                                                                                                                           |
| DMX channels:           | 3; 4; 5; 6; 10                                                                                                                                                        |
| DMX input:              | 1 x 3-pin XLR (M) mounting version IP                                                                                                                                 |
| DMX output:             | 1 x 3-pin XLR (F) mounting version IP                                                                                                                                 |
| Cooling:                | Passive convection cooling                                                                                                                                            |
| Control:                | DMX; stand-alone; IR remote control                                                                                                                                   |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; LED EASY<br>OPERATOR 4x4; LED EASY OPERATOR 4x6;<br>LED EASY OPERATOR DELUXE; Light Captain;<br>EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free                                                                                                                                                          |
| PWM frequency:          | 5800 Hz                                                                                                                                                               |
| Beam angle:             | 15°                                                                                                                                                                   |
| Beam angle (1/2 peak):  | 15°                                                                                                                                                                   |
| Housing color:          | Black                                                                                                                                                                 |
| Attachment system:      | Double bracket                                                                                                                                                        |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| Display type:            | LCD display                                             |
| Material:                | Aluminum casting                                        |
| Dimensions:              | Width: 25.5 cm<br>Depth: 15.3 cm<br>Height: 28.1 cm     |
| Weight:                  | 4.07 kg                                                 |
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0                                            |
| Diameter mounting holes: | 3 x Ø11mm                                               |
| Material:                | Metal, 2.5 mm                                           |
| Cable construction:      | 3 x 1.0 mm² H05RN-F                                     |
| Cable length:            | Approx. 1.2 m                                           |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

**ROADINGER Flightcase 4x LED IP PAR 7x8W QCL/7x9W SCL with wheels**

|                          |                                                                               |
|--------------------------|-------------------------------------------------------------------------------|
| Maximum load:            | 100 kg                                                                        |
| Aluminum profile frames: | 25 mm                                                                         |
| Case handle:             | 4 pc/pcs                                                                      |
| Stop hinge:              | 2 pc/pcs                                                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                                                      |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Use of brands:           | Branded hardware                                                              |
| Material:                | Birch multiplex                                                               |
| Color:                   | Dark brown, laminated                                                         |
| Device compartment:      | 21.5 cm x 22.5 cm x 29 cm                                                     |
| Accessory compartment:   | 10 cm x 50 cm x 29 cm                                                         |
| Inside dimensions:       | 53 cm x 50 cm x 29 cm                                                         |
| Material thickness:      | 6.5 mm                                                                        |
| Dimensions:              | Width: 62.50 cm<br>Depth: 53.50 cm<br>Height: 51.50 cm                        |
| Weight:                  | 17.75 kg                                                                      |

**Scope of delivery:**

- 1 x light effect
- 1 x mounting bracket
- 1 x power cord
- 1 x remote control
- 1 x user manual