



The article is no longer in our assortment.

Features:

EUROLITE LED IP T-Bar 16 QCL Bar

Weather-proof (IP65) bar with RGBW color mixing, incl. IR remote control

- 16 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 19 preset colors
- Can be operated in 3; 4; 5; 6; 9 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; master/slave function; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397694949

Weight: 120,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.00 m

Bulky product

ROADINGER Flightcase 12x LED Bar with wheels

Trunk case with castors, PRO version

- Universal modular system for LED bars up to 1 m length
- 3 stackable units accommodate 4 LED bars each
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 20mm with rounded edges
- 6 hinged, chromium plated case handles
- 12 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	106.10 kg
---------	-----------

EUROLITE LED IP T-Bar 16 QCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED type:	16 x 8 W high-power 4in1 RGBW (homogenous color mix)
Flash rate:	0.8 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) IP
DMX output:	3-pin XLR (F) IP
Cooling:	Passive convection cooling
Control:	DMX; master/slave function; stand-alone; IR remote control
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	2x mounting bracket

Display type:	4 digit 7-segment LED display
Dimensions:	Length: 106.50 cm Depth: 10.00 cm Height: 12.65 cm
Weight:	5.95 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase 12x LED Bar with wheels

Maximum load:	150 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	20 mm
Case handle:	6 pc/pcs
Lock:	Butterfly lock: 12 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	113 cm x 8.5 cm x 9 cm
Inside dimensions:	113 cm x 40.5 cm x 16 cm
Dimensions:	Width: 119 cm Depth: 44 cm Height: 84 cm
Weight:	34.70 kg

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 2 x mounting bracket
 2 x screw
 2 x washer