



Features:

EUROLITE LED IP T-PIX 12 HCL Bar

Weather-proof (IP65) bar with RGBAW+UV color mixing and pixel control

- DMX and power terminals intelligently designed for easy wiring
- 12 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response
- Strobe effect
- Direct color selection for 45 preset colors
- Can be operated in 6; 11; 24; 41; 77 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 25°
- With mounting bracket; with omega bracket
- LCD display
- Suitable for outdoor use
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397694956

Weight: 66,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.80 m

Bulky product

ROADINGER Flightcase 4x LED IP T-PIX 8 QCL/T-PIX 12 HCL with wheels

Trunk case with castors, PRO version

- ,
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- Branded hardware
- European engineering
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	58.00 kg
---------	----------

EUROLITE LED IP T-PIX 12 HCL Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	6; 11; 24; 41; 77
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR 4x6; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; LED EASY OPERATOR DELUXE; Colorchief
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	25°
Beam angle (1/2 peak):	25°
Beam angle (1/10 peak):	50°
Housing color:	Black

Attachment system:	2x mounting bracket Omega bracket
Display type:	LCD display
Dimensions:	Length: 99 cm Depth: 16 cm Height: 14 cm
Weight:	8.30 kg
Noise classification:	Class 0 (no noise at all)

ROADINGER Flightcase 4x LED IP T-PIX 8 QCL/T-PIX 12 HCL with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Device compartment:	100 cm x 12 cm x 17 cm
Accessory compartment:	102 cm x 10.5 cm x 17 cm
Dimensions:	Length: 106 cm Width: 74 cm Height: 40 cm
Weight:	24.80 kg

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x XLR cable
 2 x mounting bracket