



The article is no longer in our assortment.

Features:

EUROLITE LED Strip 300 5m 5050 RGB/WW/CW 24V

Flexible LED strip, RGB, warm white and cold white

- Flexible LED strip for decorative lighting
- High-grade components and a solid construction ensure excellent color rendering
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- 300 LEDs SMD 5050 4in1 RGB/WW (homogenous color mix)
- Control via system controller
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation

EUROLITE LED Strip RGB/CW/WW Zone RF Controller

5-channel wireless LED controller with remote control for RGB and dual white

- User-friendly LED controller with 4 zones (5 x 4A) and remote control
- Controls single- and multi-colored (CW+WW, RGB, RGBW) LED strips (12-24 V) as desired
- Innovative wireless technology allows multiple controllers to be controlled synchronously and asynchronously with just one remote control

Logistic

EAN / GTIN: 4026397695014

Weight: 1,50 kg

Length: 0.30 m

Width: 0.22 m

Height: 0.21 m

- Synchronous color sequences even over several hours with multiple controllers and different LED types
- Excellent signal transmission with 2.4 GHz - no perceptible difference to a wired system
- All controllers communicate with each other and cover a large range
- No visible contact between remote control and controller required
- Any number of controllers possible in 4 zones
- Color selection via touch-sensitive color wheel
- Memory function saves last setting when switching off
- Program speed adjustable; Dimmer electronic
- 9 integrated show programs
- remote control**
- Control via wireless remote control
- Operating range up to 20m

EUROLITE Electronic Transformer, 24V, 5A, IP67

Stabilized LED power supply unit DC 24 V, 5 A

- Input voltage AC 100-240 V
- Noise filter
- Suitable for outdoor use IP67

Technical specifications:

Weight:	0.91 kg
---------	---------

EUROLITE LED Strip 300 5m 5050 RGB/MW/CW 24V

Power supply:	24V DC 4800 mA
Power consumption:	115 W
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.15 m
Lamp type:	LED lamp
LED type:	300 x SMD 5050 4in1 RGB/MW (homogenous color mix)
Control:	System controller
Standing/fixation:	Self adhesive
Lamps/meter:	60 pc/pcs
Power/meter:	23 W
Lamps/tube:	300 pc/pcs
Lamp distance:	16 mm
Cutting mark:	10 cm
Luminous flux (Lumen) per meter:	950 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 1.2 cm Height: 0.2 cm
Weight:	0.15 kg
Noise classification:	Class 0 (no noise at all)

Energy efficiency class (A - G):	G
----------------------------------	---

EUROLITE LED Strip RGB/CW/WW Zone RF Controller

Power supply:	12/24V DC
Power consumption:	Max. 480 W 24 V DC Max. 240 W 12 V DC 96 W 24 V DC per channel 48 W 12 V DC per channel
Output current:	Max. 4 x 5 A per channel
Power connection:	Via screw terminal
Power output:	Screw terminal
Carrier frequency:	2.4 GHz
Dimensions:	Length: 16 cm Width: 4.6 cm Height: 2.5 cm
Weight:	0.1 kg
Battery:	2 x 1.5 V AAA Micro LR03 alkaline manganese included
Control:	Wireless remote control
Range:	Range up to 20m
Dimensions:	Length: 14.8 cm Width: 4 cm Height: 1.9 cm
Weight:	0.07 kg

EUROLITE Electronic Transformer, 24V, 5A, IP67

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP67
Protection class:	Protection class II
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0.2 m
Power output:	No connector/cable only
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	24 V DC, stabilized; 5 A;
Material:	Plastic
Dimensions:	Length: 20 cm Width: 5.2 cm Height: 3.7 cm
Weight:	0.58 kg

Scope of delivery:

1 x EUROLITE LED Strip 300 5m 5050 RGB/WW/CW 24V

- 1 x illuminant
- 1 x user manual

1 x EUROLITE LED Strip RGB/CW/WW Zone RF Controller

1 x controller
1 x remote control
1 x user manual
2 x battery
1 x declaration of conformity
1 x holder
4 x screw

1 x EUROLITE Electronic Transformer, 24V, 5A, IP67

1 x external mains adapter