

OMNITRONIC Set TRM-402 + Case

Art. No.: 20000896

GTIN: 4026397695564



List price: 712.81 €

incl. 19% VAT.

Features:

OMNITRONIC TRM-402 4-channel Rotary Mixer

4-channel rotary mixer with 3-band frequency isolator for DJs

- Classic rotary mixer with 4 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (highs/lows) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Classic ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 12-digit stereo LED level meter and master level control
- Booth output with separate level control
- Dual inputs for DJ microphone and headphones on the top and front panel
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Desktop console housing
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

Logistic

EAN / GTIN: 4026397695564

Weight: 9,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

ROADINGER Flightcase TRM-402

Carrying case, PRO version

- High-quality workmanship with birch multiplex 6.5 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Removable cover
- Aluminum profile frames 22mm with rounded edges
- Rugged carrying handle
- 2 high-quality spring locks
- Closes with a
- Rubber feet
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	7.90 kg
---------	---------

OMNITRONIC TRM-402 4-channel Rotary Mixer

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	7.2 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz microphone 20 - 20000 Hz line 40 - 18000 Hz phono
S/N ratio:	>77 dB phono >80 dB microphone >85 dB line
THD:	Line <0.03 % at 1 kHz Phono <0.1 % at 1 kHz
Gain:	Microphone 44 dB Line 20 dB Phono 60 dB to +75 dB
Isolators:	Master Gain:- ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth
Control elements:	Power switch, source selector, cue mix split function, tone control
Status LED:	Power, master level meter, channel source, CUE, microphone
Connections:	Input: line via 4 x stereo RCA Input: line/phono via 4 x stereo RCA Input: microphone via 2 x 3-pin XLR Output: headphones via 2 x 6.3 mm jack socket (stereo) mounting version

	Output: headphones via 2 x 3.5 mm jack (stereo) mounting version Output: rec. via 1 x stereo RCA Output: booth via 2 x 3-pin XLR Output: booth via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: master via 1 x stereo RCA
Channels:	Input channel: 4 x stereo with line-line/phono switch via RCA, channel control via rotary, 2-band tone control EQ, gain control, phono gain rotary, CUE switch, source selector Microphone channel: 1 x mono via XLR, channel control via rotary dial, ON AIR switch Booth output: 1 x stereo via XLR or RCA, channel control via rotary dial Master output: 1 x stereo via XLR or RCA, channel control via rotary dial Headphones output: 1 x stereo via jack, channel control via rotary dial, cue mix split function
Max. level:	Output: +22 dBu
Material:	Metal
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 33 cm Depth: 24.7 cm Height: 10.7 cm
Weight:	4.05 kg

ROADINGER Flightcase TRM-402

Maximum load:	25 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	22 mm
Carrying handle:	1 pc/pcs
Lock:	Spring lock: 2 pc/pcs
Transport aid:	Rubber feet
Use of brands:	Branded hardware
Material:	Birch multiplex, 6.5 mm
Color:	Dark brown, laminated
Device compartment:	33 cm x 23.5 cm x 4 cm
Accessory compartment:	37 cm x 6.5 cm x 4.5 cm
Inside dimensions:	37 cm x 30 cm x 4.5 cm
Dimensions:	Width: 40 cm Depth: 37 cm Height: 17.5 cm
Weight:	3.85 kg

Scope of delivery:

1 x device
1 x power cord
1 x user manual