



The article is no longer in our assortment.

Features:

EUROLITE Audience Blinder 2x100W LED COB CW/WW

Audience blinder, wide beam, warm/cold white

- Variable color temperature 3200 K - 6400 K
- Flicker-free
- Control via DMX; sound to light via microphone; master/slave function; stand-alone
- Strobe effect
- 2 LEDs 100 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
- With mounting bracket
- Energy-saving, durable and environmentally friendly
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; theater; rental
- Application possibility: Suspended; on stand
- Can be operated in 4; 8 CH mode

ROADINGER Flightcase 2x Audience Blinder 2x100W LED COB CW/WW

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 20mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks

Logistic

EAN / GTIN: 4026397697643

Weight: 16,10 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

- 1 high-quality butterfly lock
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	15.03 kg
---------	----------

EUROLITE Audience Blinder 2x100W LED COB CW/WW

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	2 x 100 W COB (chip-on-board) 2in1 CW/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	3 x cooling fan
Control:	DMX; sound to light via microphone; master/slave function; stand-alone
Fixtures available for:	Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	30°
Beam angle (1/10 peak):	80°
Color temperature:	3200K - 6400K adjustable
Luminous flux:	8500 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 37 cm Depth: 15 cm Height: 24 cm
Weight:	3.74 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	G
Cable construction:	3 x 1.5 mm² H05VV-F
Diameter mounting holes:	3 x Ø10mm

Material:	Metal, 2 mm
ROADINGER Flightcase 2x Audience Blinder 2x100W LED COB CW/WW	
Maximum load:	50 kg
Aluminum profile frames:	20 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Color:	Dark brown, laminated
Inside dimensions:	42 cm x 48 cm x 26 cm
Device compartment:	42 cm x 17.5 cm x 26 cm
Accessory compartment:	42 cm x 11 cm x 27 cm
Material thickness:	6.5 mm
Dimensions:	Length: 52 cm Width: 46 cm Height: 30.5 cm
Weight:	7.55 kg

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual