



Features:

EUROLITE LED PR-100/32 Pixel DMX rail

DMX controlled pixel tube with RGB color mixing

- DMX and power terminals intelligently designed for easy wiring
- Front cover: milky
- 96 LEDs SMD 5050 3in1 RGB (homogenous color mix)
32 segments controlled separately
- Color blend stepless; color change adjustable; colors preset; Dimmer electronic
- 12 integrated show programs
- Direct color selection for 17 preset colors
- Can be operated in 3; 5; 8; 48; 96 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397698794

Weight: 14,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

MADRIX Software 5 License start

MADRIX 5 licence "start"

- Includes 1x MADRIX 5 License "start"
- Requires a valid, empty, and metallic MADRIX KEY
- Can transmit up to 1024 DMX channels
- Compatible with Win 7, Win 8, Win 10,
- Made in Germany
- Engineered in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

MADRIX USB ONE DMX512 USB Interface

USB-DMX cable to send/receive DMX signals with MADRIX software

- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX
- Built with NEUTRIK connector
- The device can be connected via USB to the PC in connection with MADRIX software
- Compatible with Win 7, Win 8, Win 10,
- Made in Germany
- Engineered in Germany
- For application areas such as: Clubs/dancing school; stage; restaurants, bars and hotels

MADRIX KEY

MADRIX 5 KEY - without license

- Includes an empty MADRIX KEY
- Requires a proper MADRIX 5 License to activate the features or output for the MADRIX 5 Software
- The device can be connected via USB to the PC
- Made in Germany

Technical specifications:

Weight:	10.67 kg
---------	----------

EUROLITE LED PR-100/32 Pixel DMX rail

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	30 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	96 x SMD 5050 3in1 RGB (homogenous color mix)
Flash rate:	0.25 - 10 Hz
DMX channels:	3; 5; 8; 48; 96
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light Captain
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 99.9 cm Width: 5.95 cm Height: 13.2 cm
Weight:	2.10 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø11mm; 2 x Ø7mm
Material:	Metal, 2 mm

MADRIX Software 5 License start

DMX channels:	Output 1024
Weight:	0.00 kg
Operating system:	Win 7, Win 8, Win 10,

MADRIX USB ONE DMX512 USB Interface

Power supply:	5V DC 500 mA
Power connection:	Fixed power supply cord for USB A mains connection
DMX channels:	Input 512 Output 512
DMX output:	1 x 5-pin XLR (F)
Control:	DMX
USB port:	USB 2.0, type A
Use of brands:	Built with NEUTRIK connector
PC connect:	MADRIX software via USB
Weight:	0.10 kg
Operating system:	Win 7, Win 8, Win 10,

MADRIX KEY

Power connection:	Mains input via USB A (M) connectable version
USB port:	Type A
PC connect:	Via USB
Weight:	0.07 kg

Scope of delivery:

1 x light effect
1 x power cord
1 x user manual