



### Features:

#### EUROLITE LED B-40 Laser Beam Effect

LED beam effect with RGBW color mixing and RG laser

- 2 laser diodes project hundreds of red and green laser beams
- 5 LEDs 8 W SMD 9080 4in1 RGBW<BR>3 segments controlled separately
- Rotation speed stepless; color blend stepless; Dimmer electronic
- Laser; multi beam effect; strobe effect
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- 7 integrated show programs
- Can be operated in 3; 10; 22 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- With mounting bracket
- Monochrome 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; decoration; advertisement/Shop window
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397701302

Weight: 7,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

## EUROLITE SB-10 Soft Bag

Black soft bag with divider, 330 x 330 x 355 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With divider
- With Outside pocket
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 Rugged carrying handles

## Technical specifications:

|         |         |
|---------|---------|
| Weight: | 4.67 kg |
|---------|---------|

## EUROLITE LED B-40 Laser Beam Effect

|                         |                                                                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                                       |
| Power consumption:      | 65 W                                                                                                                                                                                                         |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                                             |
| Power output:           | 1 x IEC connector (F) mounting version                                                                                                                                                                       |
| Fuse:                   | 5 x 20 mm, T 1 A fuse replaceable                                                                                                                                                                            |
| Lamp type:              | LED lamp                                                                                                                                                                                                     |
| LED type:               | 5 x 8 W SMD 9080 4in1 RGBW                                                                                                                                                                                   |
| Flash rate:             | 0 - 20 Hz                                                                                                                                                                                                    |
| Laser class:            | 2M                                                                                                                                                                                                           |
| Laser color:            | R/G                                                                                                                                                                                                          |
| Laser module:           | Green (G) 40 mW 532nm<br>Red (R) 100 mW 650nm                                                                                                                                                                |
| DMX channels:           | 3; 10; 22                                                                                                                                                                                                    |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                                                                                           |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                                                                                           |
| Cooling:                | Passive convection cooling                                                                                                                                                                                   |
| Control:                | Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control |
| Fixtures available for: | Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief                                                                                                                |
| Housing color:          | Black                                                                                                                                                                                                        |
| Attachment system:      | Mounting bracket                                                                                                                                                                                             |
| Display type:           | Monochrome 4 digit 7-segment LED display                                                                                                                                                                     |
| Dimensions:             | Width: 31 cm<br>Depth: 31 cm<br>Height: 39 cm                                                                                                                                                                |

|                       |                        |
|-----------------------|------------------------|
| Weight:               | 4.20 kg                |
| Noise classification: | Class 2 (slight noise) |

#### **EUROLITE SB-10 Soft Bag**

|                  |                                               |
|------------------|-----------------------------------------------|
| Maximum load:    | 25 kg                                         |
| Carrying handle: | 2 pc/pcs                                      |
| Material:        | Nylon                                         |
| Color:           | Black, water repellent                        |
| Dimensions:      | Width: 33 cm<br>Depth: 37 cm<br>Height: 33 cm |
| Weight:          | 0.47 kg                                       |

#### **Scope of delivery:**

##### **1 x EUROLITE LED B-40 Laser Beam Effect**

1 x light effect  
1 x power cord  
1 x omega bracket  
1 x user manual  
1 x remote control  
4 x screw  
4 x washer

##### **1 x EUROLITE SB-10 Soft Bag**

1 x bag