

EUROLITE Set LED KLS Laser Bar FX Light Set white + BPS-2 Loudspeaker Stand white

GTIN: 4026397703672



Features:

EUROLITE LED KLS Laser Bar FX Light Set wh

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- Two rotating derbies for mirror ball effects with three bright LEDs (red, green and blue) each
- When fog is used, this effect becomes especially attractive
- 37 integrated show programs
- Can be operated in 3; 5; 9; 19; 27 CH mode
- The device is cooled by cooling fan
- Control via wireless footswitch; IR remote control; DMX; master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: On stand
- **laser**
- Laser

Logistic

EAN / GTIN: 4026397703672

Weight: 23,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 LEDs 3 W high-power 3in1 RGB (homogenous color mix)
 spots controlled separately
- light effect**
- 3 LEDs 1 W high-power R/G/B
- Flower effect; multi beam effect
- bar**
- 4 LEDs 1 W high-power cold white (CW)
- Strobe effect

OMNITRONIC BPS-2 Loudspeaker Stand white

Speaker and lighting stand with square base, height adjustable 110-200 cm, max. load 18 kg

- Square base plate (48 x 48 cm)
- Tube diameter: Ø 35 mm
- Carry handles and cable bushing

Technical specifications:

Weight:	18.65 kg
---------	----------

EUROLITE LED KLS Laser Bar FX Light Set wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, F 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	0 - 30 Hz
DMX channels:	3; 5; 9; 19; 27
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Wireless footswitch; IR remote control; DMX; master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
Fixtures available for:	Light´J; EASY SHOW 1; LED PC-Control 512; Light Captain; Colorchief
Housing color:	White
Attachment system:	Tube: 1x Ø 35mm 2x mounting bracket
Dimensions:	Width: 103 cm Depth: 6.1 cm Height: 38.7 cm

Weight:	9.05 kg
Noise classification:	Class 2 (slight noise)
Battery:	1 x 9.0 V E block 6LR61 alkaline manganese included
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	3 x 3 W high-power 3in1 RGB (homogenous color mix)
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	3 x 1 W high-power R/G/B
LED type:	4 x 1 W high-power cold white (CW)

OMNITRONIC BPS-2 Loudspeaker Stand white

Weight:	9.60 kg
---------	---------

Scope of delivery:

1 x device
 1 x user manual
 1 x power cord
 1 x declaration of conformity
 1 x foot control
 1 x remote control
 2 x battery
 2 x mounting bracket
 1 x bag
 2 x knurled screw
 2 x washer