

## EUROLITE Set 6x AKKU IP UP-4 Plus HCL Spot WDMX + Case with charging function

GTIN: 4026397008081



### Features:

### Logistic

EAN / GTIN: 4026397008081

#### EUROLITE AKKU IP UP-4 Plus HCL Spot WDMX

IP65 uplight with replaceable battery, RGBWA+UV LEDs, WDMX and IR remote control

- Quick and tool-free battery change, additional rechargeable battery optionally available
- Integrated W-DMX transceiver for wireless DMX Control
- Additional frost filter provides a wide, soft and homogeneous light
- Sturdy metal housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 9.5h depending on program used
- Battery pack tool-free replacement
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 10 W SMD 5050 6in1 RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 49 integrated show programs
- Direct color selection for 63 preset colors
- Can be operated in 6; 8; 12 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; W-DMX by wireless solution; master/slave function; sound to light via microphone; IR remote control
- With a beam angle of 16°

- With bracket for floor use
- Rubber feet
- Suitable for outdoor use IP65
- With a KENSINGTON LOCK theft protection
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Silent operation
- Application possibility: Standing

#### **ROADINGER Flightcase 6x AKKU IP UP-4 Plus HCL Spot WDMX with charging function**

Trunk case with castors

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

#### **Technical specifications:**

|         |          |
|---------|----------|
| Weight: | 55.16 kg |
|---------|----------|

#### **EUROLITE AKKU IP UP-4 Plus HCL Spot WDMX**

|                    |                                                                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz<br>12.6V DC 3000 mA                                                                                              |
| Pin configuration: | Inside + / outside -                                                                                                                    |
| Power consumption: | 35 W                                                                                                                                    |
| IP classification: | IP65                                                                                                                                    |
| Protection class:  | Protection class III                                                                                                                    |
| Power connection:  | Mains input via coaxial power connector (M)<br>mounting version power supply cord with AC<br>adapter (provided)<br>Battery/battery pack |
| Battery pack type: | 1 x lithium ion 11.1 V, 13000 mAh, 144.3 Wh                                                                                             |
| Battery pack:      | Battery operation up to 9.5h depending on<br>program used<br>Recharging time 8h                                                         |
| Lamp type:         | LED lamp                                                                                                                                |
| LED type:          | 4 x 10 W SMD 5050 6in1 RGBWA/UV<br>(homogenous color mix)                                                                               |
| DMX channels:      | 6; 8; 12                                                                                                                                |
| Cooling:           | Passive convection cooling                                                                                                              |
| Control:           | Stand-alone; DMX; W-DMX by wireless solution;<br>master/slave function; sound to light via<br>microphone; IR remote control             |

|                         |                                                                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Fixtures available for: | Light J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Carrier frequency:      | 2.4 GHz                                                                                                                                        |
| Beam angle:             | 16°                                                                                                                                            |
| Beam angle (1/2 peak):  | 16°                                                                                                                                            |
| Housing color:          | Black                                                                                                                                          |
| Attachment system:      | Bracket for floor use                                                                                                                          |
| Transport aid:          | Rubber feet                                                                                                                                    |
| Theft protection:       | KENSINGTON LOCK                                                                                                                                |
| Dimensions:             | Width: 17.1 cm<br>Depth: 13.8 cm<br>Height: 20 cm                                                                                              |
| Weight:                 | 4.50 kg                                                                                                                                        |
| Noise classification:   | Class 0 (no noise at all)                                                                                                                      |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese built-in                                                                                        |

#### **ROADINGER Flightcase 6x AKKU IP UP-4 Plus HCL Spot WDMX with charging function**

|                          |                                                                                              |
|--------------------------|----------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                       |
| Power connection:        | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Cable length:            | 1.2 m                                                                                        |
| Fuse:                    | 5 x 20 mm, F 5 A fuse replaceable                                                            |
| Status LED:              | Charge status indicator                                                                      |
| Aluminum profile frames: | 25 mm                                                                                        |
| Case handle:             | 4 pc/pcs                                                                                     |
| Edge mounting handle:    | 1 pc/pcs                                                                                     |
| Stop hinge:              | 2 pc/pcs                                                                                     |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function                                              |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover                |
| Material:                | Plywood multi-layer glued                                                                    |
| Color:                   | Black, laminated                                                                             |
| Device compartment:      | 17.1 cm x 15 cm x 21 cm                                                                      |
| Accessory compartment:   | 55.5 cm x 7.8 cm x 21 cm                                                                     |
| Dimensions:              | Length: 94 cm<br>Width: 48.5 cm<br>Height: 44.5 cm                                           |
| Weight:                  | 28.16 kg                                                                                     |

#### **Scope of delivery:**

##### **6 x EUROLITE AKKU IP UP-4 Plus HCL Spot WDMX**

1 x spotlight  
1 x power cord  
1 x external mains adapter  
1 x remote control

- 1 x frost filter
- 2 x screw
- 1 x plate
- 1 x user manual
- 1 x declaration of conformity
- 1 x battery
- 1 x battery pack

**1 x ROADINGER Flightcase 6x AKKU IP UP-4 Plus HCL Spot WDMX with charging function**

- 1 x case
- 1 x power cord
- 1 x user manual