



Features:

EUROLITE AKKU PAR 6 QCL

Battery-powered LED spotlight with RGBW color mixing, incl. IR remote control

- Cordless, flexible and versatile
- Battery operation up to 12h depending on program used
- Integrated automatic charging of the battery and status indicator
- 6 LEDs 4 W SMD 9080 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 6; 11 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
- Flicker-free
- With a beam angle of 18°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397720891

Weight: 6,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

EUROLITE SB-13 Soft Bag

Transport bag

- With 3 dividers
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight:	5.30 kg
---------	---------

EUROLITE AKKU PAR 6 QCL

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Battery pack type:	1 x lithium ion 14.8 V, 4400 mAh, 65.12 Wh
Battery pack:	Battery operation up to 12h depending on program used Recharging time 3.5h
Lamp type:	LED lamp
LED type:	6 x 4 W SMD 9080 4in1 RGBW (homogenous color mix)
Flash rate:	1.5 - 50 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
Fixtures available for:	Light´J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	23400 Hz
Beam angle:	18°

Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	36°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 17.7 cm Depth: 14.3 cm Height: 21.1 cm
Weight:	2.52 kg
Noise classification:	Class 0 (no noise at all)
Material:	Metal
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE SB-13 Soft Bag

Maximum load:	10 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Dimensions:	Length: 41 cm Depth: 16 cm Height: 19 cm
Weight:	0.26 kg

Scope of delivery:

2 x EUROLITE AKKU PAR 6 QCL

1 x spotlight
 1 x power cord
 1 x XLR cable
 1 x remote control
 1 x battery
 1 x user manual

1 x EUROLITE SB-13 Soft Bag

1 x bag