



### Features:

#### EUROLITE LED TMH-H240 Beam/Wash/Flower Effect

Hybrid moving head with RGBW LEDs, zoom, macros, patterns and color temperature presets

- 3in1 moving head beam, wash and flower effect in one device
- 6 LEDs 40 W 4in1 RGBW (homogenous color mix) LEDs controlled separately
- Positioning within 540° PAN, 240° TILT
- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven; lens rotation
- Color blend stepless; color change; colors preset; patterns preset; background color adjustable; Dimmer speed (step response) adjustable
- Strobe effect; fan effect; flower effect; multi beam effect
- Integrated show programs
- Can be operated in 16; 21; 24; 32; 56 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- Flicker-free
- With a beam angle of 2° - 40°
- With omega bracket

### Logistic

EAN / GTIN: 4026397699807

Weight: 28,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; stage
- Application possibility: Standing; suspended

#### ROADINGER Flightcase 2x TMH-S90/H90/B90

Trunk case with castors

- For optimal security
- With 2 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function; 2 high-quality butterfly locks
- Closes with a
- Castors

#### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 25.35 kg |
|---------|----------|

#### EUROLITE LED TMH-H240 Beam/Wash/Flower Effect

|                         |                                                                                                                                                                                                       |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                                                |
| Power consumption:      | 190 W                                                                                                                                                                                                 |
| Protection class:       | Protection class I                                                                                                                                                                                    |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                       |
| Power output:           | P-Con (grey), mounting version                                                                                                                                                                        |
| Fuse:                   | 5 x 20 mm, T 3 A                                                                                                                                                                                      |
| Lamp type:              | LED lamp                                                                                                                                                                                              |
| LED type:               | 6 x 40 W 4in1 RGBW (homogenous color mix)                                                                                                                                                             |
| Max. TILT movement:     | 240° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                                                                                     |
| Max. PAN movement:      | 540°, 360° exact positioning (16 bit resolution)<br>auto position correction (feedback)                                                                                                               |
| Flash rate:             | 1 - 20 Hz                                                                                                                                                                                             |
| Equipment:              | Zoom motor driven; lens rotation                                                                                                                                                                      |
| DMX channels:           | 16; 21; 24; 32; 56                                                                                                                                                                                    |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                                                        |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                                                        |
| Cooling:                | Temperature-controlled fan                                                                                                                                                                            |
| Control:                | Stand-alone; sound to light via microphone; DMX;<br>QuickDMX via USB (optional); W-DMX by<br>wireless solution via USB (optional); CRMX by<br>LumenRadio via USB (optional); master/slave<br>function |
| Fixtures available for: | Light Captain; EASY SHOW 3; Light J                                                                                                                                                                   |

|                          |                                                                                                                                                                                                                                                                                                   |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Projection:              | Flicker-free                                                                                                                                                                                                                                                                                      |
| PWM frequency:           | 2900 Hz                                                                                                                                                                                                                                                                                           |
| Beam angle:              | 2° - 40°                                                                                                                                                                                                                                                                                          |
| Beam angle (1/2 peak):   | 2 - 25°                                                                                                                                                                                                                                                                                           |
| Beam angle (1/10 peak):  | 8 - 40°                                                                                                                                                                                                                                                                                           |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 11423 lx, 3m: 5703 lx, 6m: 1423 lx<br>Narrow green (G) 1m: 28573 lx, 3m: 11882 lx, 6m: 2992 lx<br>Narrow blue (B) 1m: 3089 lx, 3m: 1835 lx, 6m: 513 lx<br>Narrow cold white (CW) 1m: 35392 lx, 3m: 15489 lx, 6m: 3899 lx<br>Narrow all 1m: 67721 lx, 3m: 30843 lx, 6m: 7807 lx |
| Housing color:           | Black                                                                                                                                                                                                                                                                                             |
| Attachment system:       | 2x omega bracket                                                                                                                                                                                                                                                                                  |
| Display type:            | LCD display                                                                                                                                                                                                                                                                                       |
| Dimensions:              | Width: 26 cm<br>Depth: 18 cm<br>Height: 33 cm                                                                                                                                                                                                                                                     |
| Weight:                  | 6.10 kg                                                                                                                                                                                                                                                                                           |
| Noise classification:    | Class 3 (clearly perceptible sounds)                                                                                                                                                                                                                                                              |

#### **ROADINGER Flightcase 2x TMH-S90/H90/B90**

|                          |                                                                              |
|--------------------------|------------------------------------------------------------------------------|
| Maximum load:            | 50 kg                                                                        |
| Aluminum profile frames: | 30 mm                                                                        |
| Case handle:             | 2 pc/pcs                                                                     |
| Stop hinge:              | 2 pc/pcs                                                                     |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function;<br>butterfly lock: 2 pc/pcs |
| Transport aid:           | Castors                                                                      |
| Material:                | Plywood multi-layer glued, 7 mm                                              |
| Color:                   | Black, laminated                                                             |
| Device compartment:      | 20 cm x 26 cm x 37 cm                                                        |
| Accessory compartment:   | 9.5 cm x 26 cm x 37 cm                                                       |
| Dimensions:              | Width: 57 cm<br>Depth: 31 cm<br>Height: 54 cm                                |
| Weight:                  | 13.15 kg                                                                     |

#### **Scope of delivery:**

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket  
1 x XLR cable