

**List price: 136.85 €**

incl. 19% VAT.

**Features:****Logistic**

EAN / GTIN: 4026397723106

Weight: 1,30 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

**OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz**

License-free miniature wireless microphone system, digital modulation, high ease of use

- 2 frequency banks with 20 adjustable frequencies each available
- Quick pairing at the touch of a button
- Receiver automatically adopts frequency setting
- Ultra-low latency
- Digital transmission provides for high resistance to interference and unique sound quality
- Small lightweight version
- Multiple receivers can be combined with 2 transmitters as desired
- Sample rate: 48 kHz
- Operating range up to 30m with line-of-sight
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; restaurants, bars and hotels; small rental; product presentations and lectures

**battery pack**

- Cordless, flexible and versatile
- Battery operation up to 5h

**OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz**

Dynamic hand-held microphone for FAS-TWO receiver

- Digital transmission provides for high resistance to interference and unique sound quality
- Quick pairing at the touch of a button
- 2 frequency banks with 20 adjustable frequencies each available
- Rugged, ergonomic aluminum housing
- Polar pattern: Cardioid
- Powered by a battery/battery pack
- Operating range up to 30m with line-of-sight
- UHF 660 - 690 MHz License-free and approved in large parts of Europe
- Charge status indicator

Technical specifications:

|         |         |
|---------|---------|
| Weight: | 0.76 kg |
|---------|---------|

OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz

|                      |                                                                                          |
|----------------------|------------------------------------------------------------------------------------------|
| Type:                | Receiver                                                                                 |
| Power supply:        | 100-240 V AC, 50/60 Hz<br>5V DC 1000 mA                                                  |
| Power connection:    | Mains input via USB C (W) mounting version<br>power supply cord with AC adapter included |
| Number of channels:  | 2                                                                                        |
| Frequency range:     | 60 - 15000 Hz                                                                            |
| S/N ratio:           | >92 dB                                                                                   |
| THD:                 | <0.8 % at 1 kHz                                                                          |
| Range:               | Range up to 30m with line-of-sight                                                       |
| Frequency band:      | UHF 660 - 690 MHz                                                                        |
| Modulation:          | Pi/4 DQPSK                                                                               |
| Frequency selection: | 40<br>In 2 groups<br>Frequencies automatically scannable<br>Switchable frequencies       |
| Sample rate:         | 48 kHz                                                                                   |
| Status LED:          | Power, channel source                                                                    |
| Connections:         | Output: mic/line via 1 x 3.5 mm jack (mono)                                              |
| Channels:            | Microphone channel: 2 x mono                                                             |
| Max. level:          | Output: mic/line -1.90 dBu, unbal.                                                       |
| Color:               | Black                                                                                    |
| Weight:              | 0.14 kg                                                                                  |
| Material:            | Metal                                                                                    |
| Dimensions:          | Length: 17 cm<br>Width: 3.6 cm<br>Height: 2.2 cm                                         |
| Weight:              | 0.05 kg                                                                                  |
| Power connection:    | Battery/battery pack built-in                                                            |
| Battery pack type:   | 1 x lithium ion 3.7 V, 800 mAh, 3.96 Wh                                                  |
| Battery pack:        | Battery operation up to 5h                                                               |

**OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz**

|                      |                                               |
|----------------------|-----------------------------------------------|
| Power supply:        | 3V DC                                         |
| Power connection:    | Battery/battery pack                          |
| Capsule type:        | Dynamic                                       |
| Polar pattern:       | Cardioid                                      |
| Battery:             | 2 x Mignon (AA) (not included)                |
| Range:               | Range up to 30m with line-of-sight            |
| Frequency band:      | UHF 660 - 690 MHz                             |
| RF power output:     | 10 mW                                         |
| Modulation:          | Pi/4 DQPSK                                    |
| Frequency selection: | 40 switchable frequencies<br>In 2 groups      |
| Display reading:     | Frequency , channel , charge status indicator |
| Switch:              | On/off switch                                 |
| Material:            | Metal                                         |
| Color:               | Black                                         |
| Dimensions:          | Length: 25.5 cm<br>Diameter: Ø 5.3 cm         |
| Weight:              | 0.31 kg                                       |

**Scope of delivery:****1 x OMNITRONIC FAS TWO 2-channel Wireless Receiver 660-690MHz**

1 x receiver  
1 x adapter  
1 x external mains adapter  
1 x USB cable  
1 x user manual  
1 x declaration of conformity

**2 x OMNITRONIC FAS Dynamic Wireless Microphone 660-690MHz**

1 x transmitter  
1 x user manual  
1 x declaration of conformity