



List price: 1307.81 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Scan Pro Next FX Compact Light Set

Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag

- Heart gobo for romantic occasions
- Positioning within
- Color wheel; gobo wheel with static gobos
- Program selection; Dimmer electronic; color blend stepless
- Strobe effect; multi beam effect; UV effect
- Color wheel with 7 dichroic filters plus open
- Gobo wheel with static gobos, 7 gobos and open
- 20 integrated show programs
- Can be operated in 3; 7; 13; 14; 15; 18; 19; 30; 32; 39 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; sound to light via microphone; master/slave function; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional); quick select potentiometer for brightness
- Flicker-free
- The article is delivered with practical transport bag
- The article is delivered pre-assembled
- With mounting bracket
- OLED display

Logistic

EAN / GTIN: 4026397280050

Weight: 35,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
 - Application possibility: Suspended; on stand
- spotlight**
- 5 LEDs 7 W SMD 9080 4in1 RGB/WW (homogenous color mix)
4 spots controlled separately
 - With a beam angle of 15°
- light effect**
- 2 LEDs 3 W R/G/B
- moving light**
- 1 LED 37.5 W cold white (CW)
- bar**
- 4 LEDs 1 W SMD 8072 ultra violet (UV)
 LEDs controlled separately

OMNITRONIC BPS-3 Loudspeaker Stand black

XL speaker/lighting stand with square base, height adjustable 136-230 cm, max. load 18 kg

EUROLITE STV-3529 Adapter long

Massive adapter for 35 mm tube, 28 mm TV spigot, maximum load WLL 100 kg

- For stands with telescopic tube 35 mm
- Connection element for cross beam with 28 mm TV spigot
- With M6 and M8 fixation screw
- Heavy version for highest stability
- TV spigot

Technical specifications:

Weight:	27.80 kg
---------	----------

EUROLITE LED KLS Scan Pro Next FX Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	265 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	H05VV-F
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 5 A fuse replaceable
Equipment:	Color wheel; gobo wheel with static gobos
Color generation:	Color wheel with 7 dichroic filters plus open
Gobos:	Gobo wheel with static gobos, 7 gobos and open
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan

Control:	Stand-alone; sound to light via microphone; master/slave function; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); wireless footswitch (optional); quick select potentiometer for brightness
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Housing color:	Black
Attachment system:	Tube: Ø 35mm 2x mounting bracket
Display type:	OLED display
Dimensions:	Length: 112 cm Depth: 10 cm Height: 42 cm
Weight:	13.30 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	4 x 1 W SMD 8072 ultra violet (UV)
Illuminance in Lux (lx):	Ultra violet (UV) 1m: 30 lx, 3m: 4 lx, 6m: 1 lx
LED type:	2 x 3 W R/G/B
LED type:	5 x 7 W SMD 9080 4in1 RGB/WW (homogenous color mix)
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Illuminance in Lux (lx):	Spot red (R) 1m: 2300 lx, 3m: 235 lx, 6m: 58 lx Spot green (G) 1m: 4187 lx, 3m: 422 lx, 6m: 107 lx Spot blue (B) 1m: 760 lx, 3m: 78 lx, 6m: 20 lx Spot warm white (WW) 1m: 3290 lx, 3m: 325 lx, 6m: 85 lx Spot all 1m: 10283 lx, 3m: 1010 lx, 6m: 259 lx
LED type:	Each with 1 x 37.5 W cold white (CW)

OMNITRONIC BPS-3 Loudspeaker Stand black

Weight:	13.00 kg
---------	----------

EUROLITE STV-3529 Adapter long

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	TV spigot Ø 28mm Ø 35mm
Type (general stands):	Accessory
Material:	Steel, 6 mm, powder-coated

Dimensions:	Width: 8.50 cm
	Depth: 5 cm
	Height: 19.50 cm
Weight:	1.50 kg

Scope of delivery:

1 x EUROLITE LED KLS Scan Pro Next FX Compact Light Set

1 x device
1 x user manual
1 x power cord
1 x declaration of conformity
2 x mounting bracket
1 x remote control
1 x battery
1 x bag
2 x knurled screw
2 x washer

1 x EUROLITE STV-3529 Adapter long

1 x device
1 x user manual
2 x knurled screw