



Features:

EUROLITE LED TSL-150 Scan COB

Handy scanner with 30 W COB LED, gobo and color wheel

- Compact design
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- 1 LED 30 W COB (chip-on-board) cold white (CW)
- Positioning within
- Gobo wheel with static gobos; focus manual
- Dimmer electronic
- Gobo effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
shake effect
- Integrated show programs
- Can be operated in 9 CH mode
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- With a beam angle of 12°
- LCD display
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer
- Application possibility: Standing; on stand

Logistic

EAN / GTIN: 4026397664416

Weight: 17,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 2x TSL-150/250/350

Trunk case

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	12.66 kg
---------	----------

EUROLITE LED TSL-150 Scan COB

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) cold white (CW)
Flash rate:	2 - 29 Hz
Equipment:	Gobo wheel with static gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect
DMX channels:	9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	12°
Beam angle (1/2 peak):	12°
Illuminance in Lux (lx):	Cold white (CW) 3m: 1212 lx, 6m: 309 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 16.5 cm

	Depth: 33 cm
	Height: 19.5 cm
Weight:	2.88 kg

ROADINGER Flightcase 2x TSL-150/250/350

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	19 cm x 33.5 cm x 12.5 cm
Accessory compartment:	8 cm x 33 cm x 12.5 cm
Inside dimensions:	49 cm x 33.5 cm x 12.5 cm
Dimensions:	Width: 54 cm Depth: 38 cm Height: 24 cm
Weight:	6.90 kg

Scope of delivery:

1 x light effect
 1 x user manual
 1 x power cord
 1 x mounting bracket
 2 x screw