



List price: 891.31 €

incl. 19% VAT.

Features:

Logistic

EUROLITE LED CLS-9 QCL RGB/WW 9x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

- Additional frost filter provides a wide, soft and homogeneous light
- 9 LEDs 7 W 4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 10°
- With mounting bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater
- Silent operation
- Application possibility: Standing; suspended; on stand

EAN / GTIN: 4026397710496

Weight: 17,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 2x LED CLS-9 QCL RGB/WW 9x7W

Trunk case, HIGHLINE version

- High-quality workmanship with birch multiplex 7 mm, black
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 32mm with rounded edges
- 3 hinged, chromium plated case handles
- 1 high-quality butterfly lock
- Closes with a
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	14.70 kg
---------	----------

EUROLITE LED CLS-9 QCL RGB/WW 9x7W

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	54 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey)
Lamp type:	LED lamp
LED type:	9 x 7 W 4in1 RGB/WW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 18°
Beam angle (1/10 peak):	28° Frost filter 47°
Housing color:	Black
Attachment system:	Mounting bracket

Display type:	OLED display
Dimensions:	Length: 27.1 cm Width: 14.3 cm Height: 21.3 cm
Weight:	3.20 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 2x LED CLS-9 QCL RGB/WW 9x7W

Aluminum profile frames:	32 mm
Case handle:	3 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm, laminated
Color:	Black
Dimensions:	Width: 48.5 cm Depth: 30.5 cm Height: 35 cm
Weight:	8.30 kg

Scope of delivery:

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x frost filter
- 2 x knurled screw
- 1 x remote control
- 1 x battery
- 1 x barndoor