



**List price: 2319.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE Multiflood IP 8x10W RGBW Wash

Silent IP65 LED floodlight with RGBW color mixing, diffuser cover, barn doors and IR remote control

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 8 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; IR remote control; RDM
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection

### Logistic

EAN / GTIN: 4026397527698

Weight: 55,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- For application areas such as: Architecture; stage; wedding/gala/events; Trade fair and shop fitting; theater; rental
- Silent operation
- Application possibility: Suspended; on stand; standing
- 3 buttons on the remote control for saving your own settings

#### ROADINGER Flightcase 4x Multiflood IP 8x10W RGBW Wash

Trunk case with castors

- Interior with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 2 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 50.15 kg |
|---------|----------|

#### EUROLITE Multiflood IP 8x10W RGBW Wash

|                         |                                                                                                |
|-------------------------|------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                         |
| Power consumption:      | 80 W                                                                                           |
| IP classification:      | IP65                                                                                           |
| Protection class:       | Protection class I                                                                             |
| Power connection:       | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided) |
| Power output:           | IP T-Con (F) mounting version                                                                  |
| Lamp type:              | LED lamp                                                                                       |
| LED type:               | 8 x 10 W SMD 5050 4in1 RGBW (homogenous<br>color mix)                                          |
| Flash rate:             | 0.8 - 28 Hz                                                                                    |
| DMX channels:           | 3; 4; 6; 8; 11                                                                                 |
| DMX input:              | 3-pin XLR (M) mounting version IP                                                              |
| DMX output:             | 3-pin XLR (F) mounting version IP                                                              |
| Cooling:                | Passive convection cooling                                                                     |
| Control:                | Stand-alone; DMX; master/slave function; IR<br>remote control; RDM                             |
| Fixtures available for: | Light Captain; LED PC-Control 512; Light´J;<br>Colorchief                                      |
| Projection:             | Flicker-free                                                                                   |
| Beam angle:             | 10°                                                                                            |
| Beam angle (1/2 peak):  | 10°<br>Frost filter 25°                                                                        |
| Beam angle (1/10 peak): | 25°                                                                                            |

|                       |                                                         |
|-----------------------|---------------------------------------------------------|
|                       | Frost filter 55°                                        |
| Housing color:        | Black                                                   |
| Attachment system:    | Mounting bracket<br>Omega bracket                       |
| Display type:         | OLED display                                            |
| Theft protection:     | KENSINGTON LOCK                                         |
| Dimensions:           | Length: 31.9 cm<br>Width: 14 cm<br>Height: 24.8 cm      |
| Weight:               | 6.10 kg                                                 |
| Noise classification: | Class 0 (no noise at all)                               |
| Battery:              | 1 x button cell 3.0 V CR2032 lithium manganese built-in |

**ROADINGER Flightcase 4x Multiflood IP 8x10W RGBW Wash**

|                          |                                                                               |
|--------------------------|-------------------------------------------------------------------------------|
| Aluminum profile frames: | 35 mm                                                                         |
| Case handle:             | 4 pc/pcs                                                                      |
| Edge mounting handle:    | 1 pc/pcs                                                                      |
| Stop hinge:              | 3 pc/pcs                                                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                                                      |
| Transport aid:           | 2 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Color:                   | Black, laminated                                                              |
| Device compartment:      | 15 cm x 46 cm x 30 cm                                                         |
| Accessory compartment:   | 8.5 cm x 46 cm x 30 cm                                                        |
| Material thickness:      | 9 mm                                                                          |
| Dimensions:              | Width: 87.5 cm<br>Depth: 53 cm<br>Height: 55.5 cm                             |
| Weight:                  | 25.75 kg                                                                      |

**Scope of delivery:**

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x frost filter
- 1 x omega bracket
- 1 x barndoor