



Features:

EUROLITE Multiflood IP 8x10W RGBW Wash CRMX

Silent IP65 LED floodlight with RGBW color mixing, CRMX, diffuser cover, barn doors, IR remote control

- Integrated wireless receiver for CRMX operation
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- 8 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane

Logistic

EAN / GTIN: 4026397527995

Weight: 55,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; wedding/gala/events; Trade fair and shop fitting; theater; rental
- Silent operation
- Application possibility: Suspended; on stand; standing
- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 4x Multiflood IP 8x10W RGBW Wash

Trunk case with castors

- Interior with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 2 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	50.15 kg
---------	----------

EUROLITE Multiflood IP 8x10W RGBW Wash CRMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	8 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; W-DMX by wireless solution; CRMX by LumenRadio; master/slave function; RDM; stand-alone; IR remote control
Fixtures available for:	Light Captain; LED PC-Control 512; Light´J
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	10°
Beam angle (1/2 peak):	10°

	Frost filter 25°
Beam angle (1/10 peak):	25°
	Frost filter 55°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 31.9 cm Width: 14 cm Height: 24.8 cm
Weight:	6.10 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 4x Multiflood IP 8x10W RGBW Wash

Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	2 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Device compartment:	15 cm x 46 cm x 30 cm
Accessory compartment:	8.5 cm x 46 cm x 30 cm
Material thickness:	9 mm
Dimensions:	Width: 87.5 cm Depth: 53 cm Height: 55.5 cm
Weight:	25.75 kg

Scope of delivery:

1 x device
 1 x user manual
 1 x power cord
 1 x remote control
 1 x frost filter
 1 x omega bracket
 1 x barndoor
 1 x battery