



16 x



Features:

EUROLITE LED Silent Par 6 QCL floor bk

LED floor spot with RGB/WW color mixing

- 14350 lux at 1 m
- 6 LEDs 8 W 4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 6; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
- Flicker-free
- With a beam angle of 16°
- With double bracket; with mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397687071

Weight: 80,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase BAS-1 8x SILENT PAR 6 QCL FLOOR

Trunk case with castors, HIGHLINE version

- High-quality workmanship with birch multiplex 10 mm, black, laminated
- Interior with felt cover
cover with foam padding
- Aluminum profile frames 32mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 Edge mounting handles
- 4 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe

ROADINGER Flightcase Extension 8x SILENT PAR 6 QCL FLOOR for BAS-1

- High-quality workmanship with birch multiplex 10 mm, black
- Interior with felt cover
cover with foam padding
- 4 hinged, chromium plated case handles
- 4 high-quality butterfly locks
- Closes with a
- Branded hardware
- Made in Europe

Technical specifications:

Weight:	76.58 kg
---------	----------

EUROLITE LED Silent Par 6 QCL floor bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	6 x 8 W 4in1 RGB/WW (homogenous color mix)
Flash rate:	1.5 - 30 Hz
DMX channels:	6; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone
Fixtures available for:	Light´ J; Light Captain; Colorchief
Projection:	Flicker-free

PWM frequency:	23500 Hz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	29°
Housing color:	Black
Attachment system:	Double bracket Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 14.3 cm Width: 17.7 cm Height: 21.1 cm
Weight:	2.15 kg
Noise classification:	Class 0 (no noise at all)
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 1.5 mm
Cable length:	Approx. 2 m
Color:	Black

ROADINGER Flightcase BAS-1 8x SILENT PAR 6 QCL FLOOR

Aluminum profile frames:	32 mm
Case handle:	4 pc/pcs
Edge mounting handle:	2 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 10 mm
Color:	Black, laminated
Device compartment:	14.5 cm x 15 cm x 19 cm
Accessory compartment:	65.5 cm x 11 cm x 19 cm
Dimensions:	Length: 70 cm Width: 48 cm Height: 43.5 cm
Weight:	23.75 kg

ROADINGER Flightcase Extension 8x SILENT PAR 6 QCL FLOOR for BAS-1

Case handle:	4 pc/pcs
Lock:	Butterfly lock: 4 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 10 mm
Color:	Black

Device compartment:	14.5 cm x 15 cm x 16 cm
Accessory compartment:	66 cm x 11.5 cm x 16 cm
Dimensions:	Length: 69 cm Width: 47 cm Height: 29 cm
Weight:	13.40 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x XLR cable
- 1 x user manual