

EUROLITE Set 8x AKKU Mini IP UP-4 QCL Spot MK2 + Case with charging function

001006
GTIN: 4026397711844



List price: 1486.31 €

incl. 19% VAT.

Features:

Logistic

EAN / GTIN: 4026397711844

EUROLITE AKKU Mini IP UP-4 QCL Spot MK2

Mini battery uplight IP65 with RGBW LEDs and IR remote control

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 4 W 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable
- Strobe effect; uplight effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via sound to light via microphone; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- 4 digit 7-segment LED display
- Suitable for outdoor use IP65
- For application areas such as: Architecture; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Application possibility: Standing
- Silent operation

ROADINGER Flightcase 8x AKKU Mini IP UP-4 QCL Spot MK2 with charging function

Trunk case with castors

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Technical specifications:

Weight:	22.96 kg
---------	----------

EUROLITE AKKU Mini IP UP-4 QCL Spot MK2

Power supply:	5V 1600 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via USB C (W) mounting version
Battery pack type:	1 x lithium ion 11.1 V, 3200 mAh, 35.52 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 5h
Lamp type:	LED lamp
LED type:	4 x 4 W 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
Cooling:	Passive convection cooling
Control:	Sound to light via microphone; stand-alone; IR remote control
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 10 cm Width: 11 cm Height: 12 cm
Weight:	1.17 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell CR2025

ROADINGER Flightcase 8x AKKU Mini IP UP-4 QCL Spot MK2 with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug included
Fuse:	5 x 20 mm, F 10 A fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Device compartment:	11.5 cm x 10.5 cm x 10 cm
Accessory compartment:	52 cm x 8 cm x 10 cm
Inside dimensions:	52 cm x 41 cm x 10 cm
Material thickness:	9 mm
Dimensions:	Width: 56.5 cm Depth: 45.5 cm Height: 29.5 cm
Weight:	13.60 kg
Cable length:	1.15 m

Scope of delivery:**8 x EUROLITE AKKU Mini IP UP-4 QCL Spot MK2**

1 x light effect
1 x remote control
1 x USB cable
1 x user manual

1 x ROADINGER Flightcase 8x AKKU Mini IP UP-4 QCL Spot MK2 with charging function

1 x case
1 x power cord
1 x user manual
4 x castors