

## FUTURELIGHT Set 4x EYE-740 MK2 + Case with wheels

Art. No.: 20001009

GTIN: 4026397695748



**List price: 5948.81 €**

incl. 19% VAT.

### Features:

#### FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash

PRO Washlight with 40 W Osram Ostar RGBW LEDs, large zoom range and pixel control

- Compact lightweight
- Crossfade channel from any color to white
- Number of scenes can be changed individually
- 7 LEDs 40 W 4in1 RGBW (homogenous color mix)<BR> LEDs controlled separately
- OSRAM LED installed
- Positioning within 540° PAN, 210° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, color, zoom
- Zoom motor driven
- Patterns animated; dimmer curves with adjustable response; pulse-width modulation variable; pulse effect adjustable; white balance; scenes user-definable; CTO correction filter virtual; Dim to warm; colors preset; Dimmer speed (step response) adjustable
- Strobe effect
- Can be operated in 18; 25; 37; 26; 33; 45; 46; 53; 65 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone

### Logistic

EAN / GTIN: 4026397695748

Weight: 78,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Flicker-free
- With a beam angle of 1° - 48°
- Variable color temperature 2800 K - 10000 K
- With omega bracket
- Multicolor LCD display,<BR>with battery buffering for easy controlling upgradeable
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; stage; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended

#### **ROADINGER Flightcase 4x EYE-740 MK2 with wheels**

Trunk case with castors

- With 4 device compartments
- With 1 accessory compartment
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes

#### **Technical specifications:**

---

|         |          |
|---------|----------|
| Weight: | 76.90 kg |
|---------|----------|

---

#### **FUTURELIGHT EYE-740 MK2 QCL Zoom LED Moving Head Wash**

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                              |
| Power consumption:  | 210 W                                                                               |
| Protection class:   | Protection class I                                                                  |
| Power connection:   | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug |
| Power output:       | IP T-Con (F) mounting version                                                       |
| Fuse:               | 5 x 20 mm, T 2 A fuse replaceable                                                   |
| Lamp type:          | LED lamp                                                                            |
| LED type:           | 7 x 40 W 4in1 RGBW (homogenous color mix)                                           |
| LED manufacturer:   | OSRAM                                                                               |
| Max. TILT movement: | 210° exact positioning (16 bit resolution) auto<br>position correction (feedback)   |
| Max. PAN movement:  | 540° exact positioning (16 bit resolution) auto<br>position correction (feedback)   |
| Flash rate:         | 0.5 - 16 Hz                                                                         |
| Equipment:          | Zoom motor driven                                                                   |
| DMX channels:       | 18; 25; 37; 26; 33; 45; 46; 53; 65                                                  |
| DMX input:          | 3-pin XLR (M) mounting version<br>5-pin XLR (M) mounting version                    |
| DMX output:         | 3-pin XLR (F) mounting version                                                      |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          | 5-pin XLR (F) mounting version                                                                                                                                                                                                                                                                                                                                                                                                           |
| Cooling:                 | Temperature-controlled fan                                                                                                                                                                                                                                                                                                                                                                                                               |
| Control:                 | Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone                                                                                                                                                                                                           |
| Fixtures available for:  | Light Captain; GDTF (GrandMA3)                                                                                                                                                                                                                                                                                                                                                                                                           |
| Projection:              | Flicker-free                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Beam angle:              | 1° - 48°                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Beam angle (1/2 peak):   | 1 - 32°                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Beam angle (1/10 peak):  | 5 - 48°                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Color temperature:       | 2800K - 10000K adjustable                                                                                                                                                                                                                                                                                                                                                                                                                |
| Illuminance in Lux (lx): | Narrow red (R) 3m: 6818 lx, 6m: 1758 lx<br>Narrow green (G) 3m: 12807 lx, 6m: 3122 lx<br>Narrow blue (B) 3m: 2513 lx, 6m: 21580 lx<br>Narrow cold white (CW) 3m: 21580 lx, 6m: 5431 lx<br><br>Narrow all 3m: 38576 lx, 6m: 9662 lx<br>Wide red (R) 3m: 162 lx, 6m: 46 lx<br>Wide green (G) 3m: 315 lx, 6m: 89 lx<br>Wide blue (B) 3m: 85 lx, 6m: 25 lx<br>Wide cold white (CW) 3m: 504 lx, 6m: 143 lx<br>Wide all 3m: 915 lx, 6m: 259 lx |
| Housing color:           | Black                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Attachment system:       | Omega bracket                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Display type:            | Multicolor LCD display battery buffering upgradeable                                                                                                                                                                                                                                                                                                                                                                                     |
| Transport aid:           | Rubber feet                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Dimensions:              | Width: 28.6 cm<br>Depth: 24.5 cm<br>Height: 37.2 cm                                                                                                                                                                                                                                                                                                                                                                                      |
| Weight:                  | 8.10 kg                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-sensitive environments)                                                                                                                                                                                                                                                                                                                                                                   |

#### **ROADINGER Flightcase 4x EYE-740 MK2 with wheels**

|                          |                                   |
|--------------------------|-----------------------------------|
| Maximum load:            | 100 kg                            |
| Aluminum profile frames: | 30 mm                             |
| Case handle:             | 4 pc/pcs                          |
| Stop hinge:              | 3 pc/pcs                          |
| Lock:                    | Butterfly lock: 2 pc/pcs          |
| Transport aid:           | 4 x castors with 2 locking brakes |
| Material:                | Plywood multi-layer glued, 7 mm   |
| Color:                   | Black, laminated                  |
| Inside dimensions:       | 81 cm x 53.5 cm x 36.5 cm         |
| Device compartment:      | 28 cm x 17.5 cm x 36.5 cm         |

|                        |                                               |
|------------------------|-----------------------------------------------|
| Accessory compartment: | 10.5 cm x 53.5 cm x 36 cm                     |
| Dimensions:            | Width: 87 cm<br>Depth: 60 cm<br>Height: 63 cm |
| Weight:                | 39.35 kg                                      |

**Scope of delivery:**

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x XLR cable