

## FUTURELIGHT Set 2x EYE-1940 QCL Zoom + Case with wheels

Art. No.: 20001011

GTIN: 4026397696431



**List price: 5353.81 €**

incl. 19% VAT.

### Features:

### Logistic

EAN / GTIN: 4026397696431

#### FUTURELIGHT EYE-1940 QCL Zoom LED Moving Head Wash

PRO Washlight with 19 Osram Ostar 40W RGBW LEDs, large zoom range and pixel control

- 19 LEDs 40 W 4in1 RGBW (homogenous color mix)<BR> LEDs controlled separately
- OSRAM LED installed
- Positioning within 540° PAN, 230° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, color, zoom
- Zoom motor driven
- Patterns animated; dimmer curves with adjustable response; pulse-width modulation variable; pulse effect adjustable; white balance; scenes user-definable; CTO correction filter virtual; Dim to warm; colors preset; Dimmer speed (step response) adjustable
- Can be operated in 18; 25; 37; 30; 49; 94; 101; 113 CH mode
- The device is cooled by temperature-controlled fan at the head; low-noise cooling fan at the base
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone
- Flicker-free
- With a beam angle of 1° - 42°
- Variable color temperature 2800 K - 10000 K

- With omega bracket
- Multicolor LCD display,<BR>with battery buffering for easy controlling upgradeable
- Rubber feet
- Mains input and output for power linking up to 4 units
- For application areas such as: Wedding/gala/events; stage; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended

#### **ROADINGER Flightcase 2x EYE-1940 with wheels**

Trunk case with castors

- With 1 accessory compartment
- With 2 device compartments
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### **Technical specifications:**

##### **FUTURELIGHT EYE-1940 QCL Zoom LED Moving Head Wash**

|                     |                                                                                     |
|---------------------|-------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                              |
| Power consumption:  | 530 W                                                                               |
| Protection class:   | Protection class I                                                                  |
| Power connection:   | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug |
| Power output:       | IP T-Con (F) mounting version                                                       |
| Fuse:               | 5 x 20 mm, T 3.15 A fuse replaceable                                                |
| Lamp type:          | LED lamp                                                                            |
| LED type:           | 19 x 40 W 4in1 RGBW (homogenous color mix)                                          |
| LED manufacturer:   | OSRAM                                                                               |
| Max. TILT movement: | 230° exact positioning (16 bit resolution) auto<br>position correction (feedback)   |
| Max. PAN movement:  | 540° exact positioning (16 bit resolution) auto<br>position correction (feedback)   |
| Flash rate:         | 1 - 16 Hz                                                                           |
| Equipment:          | Zoom motor driven                                                                   |
| DMX channels:       | 18; 25; 37; 30; 37; 49; 94; 101; 113                                                |
| DMX input:          | 3-pin XLR (M) mounting version IP<br>5-pin XLR (M) mounting version IP              |
| DMX output:         | 3-pin XLR (F) mounting version IP<br>5-pin XLR (F) mounting version IP              |
| Cooling:            | 2 x temperature-controlled fan at the head<br>1 x low-noise cooling fan at the base |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Control:                 | Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by LumenRadio upgradeable; RDM; sound to light via microphone                                                                                                                                                                                                                                                                                                                                        |
| Fixtures available for:  | Light Captain; GDTF (GrandMA3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Projection:              | Flicker-free                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Beam angle:              | 1° - 42°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Beam angle (1/2 peak):   | 1 - 24°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Beam angle (1/10 peak):  | 5 - 42°                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Color temperature:       | 2800K - 10000K adjustable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 15042 lx, 3m: 11510 lx, 6m: 3434 lx<br>Narrow green (G) 1m: 30205 lx, 3m: 19403 lx, 6m: 5390 lx<br>Narrow blue (B) 1m: 5115 lx, 3m: 3767 lx, 6m: 1836 lx<br>Narrow cold white (CW) 1m: 67510 lx, 3m: 42444 lx, 6m: 11973 lx<br>Narrow all 3m: 69714 lx, 6m: 20470 lx<br>Wide red (R) 1m: 4425 lx, 3m: 533 lx, 6m: 141 lx<br>Wide green (G) 1m: 6498 lx, 3m: 823 lx, 6m: 226 lx<br>Wide blue (B) 1m: 1972 lx, 3m: 321 lx, 6m: 90 lx<br>Wide cold white (CW) 1m: 14186 lx, 3m: 1779 lx, 6m: 491 lx<br>Wide all 1m: 24550 lx, 3m: 3126 lx, 6m: 865 lx |
| Housing color:           | Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Attachment system:       | Omega bracket                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Display type:            | Multicolor LCD display battery buffering upgradeable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Transport aid:           | Rubber feet                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Dimensions:              | Width: 40 cm<br>Depth: 28 cm<br>Height: 42.2 cm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Weight:                  | 17.10 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-sensitive environments)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

#### **ROADINGER Flightcase 2x EYE-1940 with wheels**

|                          |                                                                               |
|--------------------------|-------------------------------------------------------------------------------|
| Maximum load:            | 100 kg                                                                        |
| Aluminum profile frames: | 30 mm                                                                         |
| Case handle:             | 4 pc/pcs                                                                      |
| Stop hinge:              | 2 pc/pcs                                                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                                                      |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover |
| Color:                   | Black, laminated                                                              |
| Accessory compartment:   | 60 cm x 11.5 cm x 39 cm                                                       |

|                     |                                                 |
|---------------------|-------------------------------------------------|
| Device compartment: | 29 cm x 40.5 cm x 39 cm                         |
| Material thickness: | 10 mm                                           |
| Dimensions:         | Width: 65 cm<br>Depth: 60 cm<br>Height: 65.5 cm |
| Weight:             | 29.60 kg                                        |

**Scope of delivery:**

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 2 x omega bracket
- 1 x XLR cable