



Features:

EUROLITE AKKU IP TL-3 QCL Trusslight CRMX

Weather-proof battery LED spot (IP65) ideal as trusslight or uplight with bright 3x10W RGBW LED

- Integrated wireless receiver for CRMX operation
- Compact and bright
- Additional frost filter provides a wide, soft and homogeneous light
- Threaded inserts for suspended installation
- Cordless, flexible and versatile
- Battery operation up to 10h depending on program used
- 3 LEDs 10 W 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance; Energy-saving mode
- Uplight effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; IR remote control; DMX; CRMX by LumenRadio; W-DMX by wireless solution; RDM
- Flicker-free
- With a beam angle of 8°
- OLED display

Logistic

EAN / GTIN: 4026397089141

Weight: 38,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Display of the remaining battery life for the current setting
- Charge status indicator
- Rubber feet
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Clubs/dancing school; stage; decoration; wedding/gala/events; mobile djs / entertainer; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 6x AKKU IP TL-3 QCL Trusslight CRMX with charging function and wheels

Trunk case with castors

- With 1 accessory compartment
- With 6 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes

Technical specifications:

Weight:	35.72 kg
---------	----------

EUROLITE AKKU IP TL-3 QCL Trusslight CRMX

Power supply:	100-240 V AC, 50/60 Hz 16.8V 3150 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery/battery pack
Cable length:	1.5 m detachable
Battery pack type:	1 x lithium ion 14.8 V, 5200 mAh, 76.96 Wh
Battery pack:	Battery operation up to 10h depending on program used Recharging time 3.5h
Lamp type:	LED lamp
LED type:	3 x 10 W 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling

Control:	Stand-alone; master/slave function; IR remote control; DMX; CRMX by LumenRadio; W-DMX by wireless solution; RDM
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	8°
Beam angle (1/2 peak):	8° Frost filter 20°
Beam angle (1/10 peak):	16° Frost filter 40°
Housing color:	Black
Attachment system:	2x M10 thread
Display type:	OLED display
Display reading:	Battery runtime calculation , charge status indicator
Transport aid:	Rubber feet
Dimensions:	Length: 13 cm Depth: 11.5 cm Height: 15.3 cm
Weight:	2.24 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 6x AKKU IP TL-3 QCL Trusslight CRMX with charging function and wheels

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Cable length:	1.2 m
Fuse:	5 x 20 mm, F 5 A fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	16 cm x 15 cm x 21 cm
Inside dimensions:	66.5 cm x 46 cm x 21 cm
Accessory compartment:	55 cm x 11 cm x 16 cm
Dimensions:	Length: 72.00 cm Depth: 52.00 cm Height: 48.30 cm
Weight:	20.85 kg

Scope of delivery:

6 x EUROLITE AKKU IP TL-3 QCL Trusslight CRMX

- 1 x device
- 1 x user manual
- 1 x external mains adapter
- 1 x frost filter
- 3 x knurled screw
- 1 x remote control
- 1 x battery

1 x ROADINGER Flightcase 6x AKKU IP TL-3 QCL Trusslight CRMX with charging function and wheels

- 1 x case
- 1 x power cord
- 1 x user manual
- 4 x screw