



Features:

EUROLITE LED TMH Bar S120 Moving Head Spots

LED lighting system with 4 individually controllable 30 W moving heads

- Crossbar with integrated DMX control unit and stand sleeve
- 4 LEDs 30 W COB (chip-on-board)
- Positioning within 540° PAN, 180° TILT
- Exact positioning (16 bit resolution)
- Gobo wheel with static gobos; focus manual; color wheel
- Dimmer electronic
- Strobe effect; beam effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with static gobos, 7 gobos and open
shake effect
- Can be operated in 3; 5; 9; 11; 17; 21; 30; 38 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 13°
- With omega bracket
- 4 digit 7-segment LED display

Logistic

EAN / GTIN: 4026397739435

Weight: 54,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

ROADINGER Flightcase 2x LED TMH Bar-S120 with wheels

Trunk case with castors

- With 2 device compartments
- With 2 accessory compartments
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	47.85 kg
---------	----------

EUROLITE LED TMH Bar S120 Moving Head Spots

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	4 x 30 W COB (chip-on-board)
Max. TILT movement:	180° positioning; exact positioning (16 bit resolution)
Max. PAN movement:	540° positioning; exact positioning (16 bit resolution)
Flash rate:	2 - 14 Hz
Equipment:	Gobo wheel with static gobos; focus manual; color wheel
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with static gobos, 7 gobos and open Shake effect
DMX channels:	3; 5; 9; 11; 17; 21; 30; 38
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version

Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Colorchief; Light´J; Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
PWM frequency:	11000 Hz
Beam angle:	13°
Beam angle (1/2 peak):	13°
Color temperature:	7300K
Illuminance in Lux (lx):	Cold white (CW) 1m: 8899 lx, 3m: 856 lx, 6m: 205 lx
Housing color:	Black
Attachment system:	2x omega bracket Tube: Ø 35mm
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 100.0 cm Depth: 17.5 cm Height: 28.0 cm
Weight:	13.00 kg
Noise classification:	Class 3 (clearly perceptible sounds)

ROADINGER Flightcase 2x LED TMH Bar-S120 with wheels

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Material:	Plywood multi-layer glued
Color:	Black, laminated
Device compartment:	100 cm x 14 cm x 30 cm
Accessory compartment:	49.5 cm x 8 cm x 30 cm
Inside dimensions:	100 cm x 40 cm x 30 cm
Dimensions:	Width: 106 cm Depth: 45 cm Height: 49 cm
Weight:	21.85 kg

Scope of delivery:

1 x moving light
 1 x user manual
 1 x power cord
 2 x omega bracket

2 x safety eyelet