



### Features:

#### EUROLITE LED PLL-576 CW/WW Panel

DMX-controlled surface light with 576 dual white LEDs, QuickDMX port, diffuser and barn doors

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- With a beam angle of 120°
- Variable color temperature 3000 K - 6000 K
- Very high color rendering index (CRI)
- Very quiet working noise
- Flicker-free
- Control via DMX; master/slave function; stand-alone; quick select potentiometer for brightness and color temperature; CRMx by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Direct color temperature selection for 69 preset values
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; standing; on stand
- Can be operated in 2-1; 2-2; 3-1; 3-2; 4 CH mode

### Logistic

EAN / GTIN: 4026397739589

Weight: 47,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase 4x PLL-576 CW/WW with wheels

Trunk case with castors, PRO version

- With 4 device compartments
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 6.5 mm, black
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- Branded hardware

Technical specifications:

|         |          |
|---------|----------|
| Weight: | 45.20 kg |
|---------|----------|

EUROLITE LED PLL-576 CW/WW Panel

|                              |                                                                                                                                                                                                                                         |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                                  |
| Power consumption:           | 160 W                                                                                                                                                                                                                                   |
| Protection class:            | Protection class I                                                                                                                                                                                                                      |
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                                                                                                    |
| Power output:                | 1 x P-Con (grey), mounting version                                                                                                                                                                                                      |
| Fuse:                        | T 3.15 A fuse fix in power supply                                                                                                                                                                                                       |
| Lamp type:                   | LED lamp                                                                                                                                                                                                                                |
| LED type:                    | 288 x 0.5 W SMD 5730 cold white (CW)<br>288 x 0.5 W SMD 5730 warm white (WW)                                                                                                                                                            |
| DMX channels:                | 2-1; 2-2; 3-1; 3-2; 4                                                                                                                                                                                                                   |
| DMX input:                   | 3-pin XLR (M) mounting version<br>5-pin XLR (M) mounting version                                                                                                                                                                        |
| DMX output:                  | 3-pin XLR (F) mounting version<br>5-pin XLR (F) mounting version                                                                                                                                                                        |
| Cooling:                     | Temperature-controlled fan                                                                                                                                                                                                              |
| Control:                     | DMX; master/slave function; stand-alone; quick<br>select potentiometer for brightness and color<br>temperature; CRMX by LumenRadio via USB<br>(optional); QuickDMX via USB (optional); W-DMX<br>by wireless solution via USB (optional) |
| Fixtures available for:      | Light Captain                                                                                                                                                                                                                           |
| Projection:                  | Flicker-free                                                                                                                                                                                                                            |
| Beam angle:                  | 120°                                                                                                                                                                                                                                    |
| Beam angle (1/2 peak):       | 120°                                                                                                                                                                                                                                    |
| Color temperature:           | 3000K - 6000K adjustable                                                                                                                                                                                                                |
| Color rendering index (CRI): | 93 Ra                                                                                                                                                                                                                                   |

|                          |                                                                        |
|--------------------------|------------------------------------------------------------------------|
| Illuminance in Lux (lx): | Cold white (CW) 1m: 3752 lx, 3m: 453 lx, 6m: 134 lx                    |
|                          | Warm white (WW) 1m: 3664 lx, 3m: 445 lx, 6m: 132 lx                    |
|                          | All 1m: 5667 lx, 3m: 690 lx, 6m: 204 lx                                |
| Housing color:           | Black                                                                  |
| Attachment system:       | Mounting bracket                                                       |
| Display type:            | LCD display                                                            |
| Transport aid:           | Rubber feet                                                            |
| Dimensions:              | Length: 44 cm                                                          |
|                          | Width: 19.8 cm                                                         |
|                          | Height: 22.3 cm                                                        |
| Weight:                  | 6.00 kg                                                                |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-sensitive environments) |

**ROADINGER Flightcase 4x PLL-576 CW/WW with wheels**

|                          |                                    |
|--------------------------|------------------------------------|
| Maximum load:            | 50 kg                              |
| Aluminum profile frames: | 25 mm                              |
| Case handle:             | 2 pc/pcs                           |
| Stop hinge:              | 2 pc/pcs                           |
| Lock:                    | Butterfly lock: 2 pc/pcs           |
| Transport aid:           | 4 x castors with 2 locking brakes  |
| Use of brands:           | Branded hardware                   |
| Material:                | Birch multiplex, 6.5 mm, laminated |
| Color:                   | Black                              |
| Device compartment:      | 22.5 cm x 47 cm x 25 cm            |
| Inside dimensions:       | 100 cm x 47 cm x 25 cm             |
| Accessory compartment:   | 7 cm x 47 cm x 25 cm               |
| Dimensions:              | Width: 1.045 cm                    |
|                          | Depth: 51.5 cm                     |
|                          | Height: 29.5 cm                    |
| Weight:                  | 18.90 kg                           |

**Scope of delivery:**

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x frost filter
- 4 x knurled screw