

EUROLITE Set 4x AKKU Multiflood IP 18x10W RGBW Wash CRMX + Case with wheels 34

GTIN: 4026397709612



Features:

EUROLITE AKKU Multiflood IP 18x10W RGBW Wash CRMX

Silent battery-powered IP65 floodlight with RGBW LEDs, CRMX, diffuser cover, barn doors, IR remote control

- Integrated wireless receiver for CRMX operation
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Cordless, flexible and versatile
- Battery operation up to 5.5h depending on program used
- 18 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; W-DMX by wireless solution; stand-alone; CRMX by LumenRadio; DMX; RDM; master/slave function
- Flicker-free
- With a beam angle of 10°
- With mounting bracket; with omega bracket

Logistic

EAN / GTIN: 4026397709612

Weight: 50,20 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Stage; architecture; wedding/gala/events; Trade fair and shop fitting; theater; rental
- Silent operation
- Application possibility: Suspended; on stand; standing
- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 4x AKKU Multiflood IP 18x10W RGBW Wash CRMX with charging function

Trunk case with castors

- With 4 device compartments
- With 1 accessory compartment
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- With title block

Technical specifications:

Weight:	45.20 kg
---------	----------

EUROLITE AKKU Multiflood IP 18x10W RGBW Wash CRMX

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug Battery/battery pack
Power output:	IP T-Con (F) mounting version
Battery pack type:	1 x lithium ion 29.6 V, 12.5 mAh, 370 Wh
Battery pack:	Battery operation up to 5.5h depending on program used Recharging time 2.5h
Lamp type:	LED lamp
LED type:	18 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (F) mounting version IP 5-pin XLR (M) mounting version IP

DMX output:	3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	IR remote control; W-DMX by wireless solution; stand-alone; CRMX by LumenRadio; DMX; RDM; master/slave function
Fixtures available for:	Light J; Light Captain; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 40°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	Mounting bracket Omega bracket
Display type:	OLED display
Display reading:	Battery runtime calculation , charge status indicator
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 41 cm Width: 18.4 cm Height: 26.9 cm
Weight:	12.05 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 4x AKKU Multiflood IP 18x10W RGBW Wash CRMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Cable length:	1.2 m
Fuse:	5 x 20 mm, F 5 A fuse replaceable
Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Accessory compartment:	10 cm x 51 cm x 36 cm
Device compartment:	19 cm x 51 cm x 36 cm
Material thickness:	9 mm
Dimensions:	Width: 115 cm

Depth: 58 cm
Height: 58 cm

Weight: 35.40 kg

Scope of delivery:

4 x EUROLITE AKKU Multiflood IP 18x10W RGBW Wash CRMX

1 x device
1 x user manual
1 x power cord
1 x declaration of conformity
1 x frost filter
1 x barndoor
1 x omega bracket
1 x remote control

1 x ROADINGER Flightcase 4x AKKU Multiflood IP 18x10W RGBW Wash CRMX with charging function

1 x case
1 x power cord
1 x user manual