



Features:

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

- Additional frost filter provides a wide, soft and homogeneous light
- 18 LEDs 7 W 4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 11°
- Direct color temperature selection for 3100 preset values
- With mounting bracket
- OLED display
- Rubber feet
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; party room
- Very quiet working noise

Logistic

EAN / GTIN: 4026397733020

Weight: 22,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings
knurled screw
- M4 thread

ROADINGER Flightcase 2x LED CLS-18 QCL RGB/WW

Trunk case

- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	20.57 kg
---------	----------

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	104 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	1 x PowerCON (grey)
Lamp type:	LED lamp
LED type:	18 x 7 W 4in1 RGB/WW (homogenous color mix)
Flash rate:	0.8 - 22 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
Fixtures available for:	Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11° Frost filter 15°
Beam angle (1/10 peak):	26°

	Frost filter 37°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Length: 39.6 cm Width: 14.3 cm Height: 21.3 cm
Weight:	4.86 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Diameter mounting holes:	3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm
Material:	Metal, 2 mm
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m
Diameter mounting holes:	4 x Ø4.5mm
Material:	Plastic, 2 mm
Dimensions:	Width: 28.3 cm Height: 11.6 cm
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Material:	Metal, 0.8 mm
Dimensions:	Width: 46.5 cm Height: 28.5 cm
Thread:	M4 thread x 8 mm

ROADINGER Flightcase 2x LED CLS-18 QCL RGB/WW

Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x rubber feet
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	12 cm x 40 cm x 28 cm
Accessory compartment:	10.5 cm x 47 cm x 28 cm
Dimensions:	Width: 51.5 cm Depth: 52.5 cm Height: 35.5 cm
Weight:	10.85 kg

Scope of delivery:

1 x device
 1 x power cord
 1 x frost filter
 1 x remote control
 1 x battery

4 x knurled screw
1 x user manual