



Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Bright battery powered LED uplight with 10 W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color fade adjustable speed; color change adjustable speed; white balance adjustable; color blend adjustable; frost filter; color selection manual; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Multi beam effect; spot effect; wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM
- Flicker-free
- QuickDMX: operating range up to 600m in the open air
- Up to 6 transmitters can be operated in parallel without interference

Logistic

EAN / GTIN: 4026397710106

Weight: 19,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- With a beam angle of 7°
- With bracket for floor use
- Monochrome OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- Mains input and output for power linking up to 8 units
- With a KENSINGTON LOCK theft protection
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

Carrying case

- With 4 device compartment
- High-quality workmanship with plastic , black
- Interior with foam padding
cover with foam padding
- Rugged carrying handle
- 4 high-quality spring locks with shut-off function
- Closes with a
- 4 x plastic feet
- For application areas such as: Rental; mobile djs / entertainer

Technical specifications:

Weight:	16.02 kg
---------	----------

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1.0 mm² H05VV-F
Power output:	P-Con (grey), mounting version
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
Flash rate:	0.8 - 27 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM

Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	3000 Hz
Range:	QuickDMX: range up to 600m in the open air
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
DMX fail mode:	Blackout; hold; static; full on
Beam angle:	7°
Beam angle (1/2 peak):	7° Frost filter 20°
Beam angle (1/10 peak):	18° Frost filter 42°
Attachment system:	Bracket for floor use
Display type:	Monochrome OLED display
Display reading:	Battery runtime calculation , charge status indicator
Material:	Metal, painted
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 15.4 cm Width: 13.3 cm Height: 15.8 cm
Weight:	2.93 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

Maximum load:	25 kg
Carrying handle:	1 pc/pcs
Lock:	Spring lock: 4 pc/pcs with shut-off function
Transport aid:	4 x plastic feet
Material:	Plastic
Color:	Black
Inside dimensions:	49 cm x 36 cm x 13 cm
Device compartment:	16 cm x 13.5 cm x 16 cm
Accessory compartment:	8 cm x 30.5 cm x 16 cm
Dimensions:	Length: 55 cm Depth: 42.5 cm Height: 21 cm
Weight:	4.30 kg

Scope of delivery:

4 x EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

- 1 x spotlight
- 1 x user manual

1 x declaration of conformity
1 x power cord
1 x remote control
1 x battery
1 x frost filter
1 x knurled screw

1 x ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

1 x case