




Features:

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Battery-powered IP pixel tube with RGB/CW/WW color mixing, 360° beam angle and CRMX receiver

- Integrated wireless receiver for CRMX operation
- Cordless, flexible and versatile
- Battery operation up to 8.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 144 LEDs 0.5 W SMD 5050 5in1 RGB/CW/WW (homogenous color mix)
24 segments controlled separately
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend adjustable; color macros preset; white balance adjustable; program selection manual; color animations with two adjustable colors; Emergency lighting function in case of power failure adjustable; Energy-saving mode
- 53 integrated show programs
- Direct color selection for 37 preset colors
- Can be operated in 4; 5; 7; 14; 16; 20.1; 20.2; 22.1; 22.2; 24.1; 24.2; 120; 124 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; CRMX by LumenRadio
- Flicker-free
- With a beam angle of 360°
- Good color rendering index (CRI)
- With holding clip

Logistic

EAN / GTIN: 4026397748147

Weight: 28,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Monochrome OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; rental; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended
- Silent operation
- 3 buttons on the remote control for saving your own settings

ROADINGER Plastic Case for 4x AKKU IP Pixel Tube 360° CRMX

Carrying case

- Trolley
- With 4 device compartments
- With accessory compartment
- Interior with foam padding
cover with foam padding
- 3 hinged, chromium plated case handles
- 1 hinge strap
- 8 high-quality spring locks with shut-off function
- For application areas such as: Wedding/gala/events; mobile djs / entertainer
- Closes with a

Technical specifications:

Weight:	26.50 kg
---------	----------

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Power supply:	100-240 V AC, 50/60 Hz 13V DC 3000 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC unit (provided) Battery/battery pack
Cable construction:	2 x 0.75 mm² H03VVH2-F
Battery pack type:	1 x lithium ion 10.8 V, 9000 mAh, 97.2 Wh
Battery pack:	Battery operation up to 8.5h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	144 x 0.5 W SMD 5050 5in1 RGB/CW/WW (homogenous color mix)
Flash rate:	2 - 20 Hz
DMX channels:	4; 5; 7; 14; 16; 20.1; 20.2; 22.1; 22.2; 24.1; 24.2; 120; 124
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; CRMX by LumenRadio

Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	12600 Hz
Carrier frequency:	2.4 GHz
Modulation:	GFSK
DMX fail mode:	Hold; blackout; static; full on
Beam angle:	360°
Beam angle (1/2 peak):	360°
Beam angle (1/10 peak):	360°
Color rendering index (CRI):	84 Ra
Housing color:	Black matte
Attachment system:	2x holding clip M10 thread
Display type:	Monochrome OLED display
Display reading:	Charge status indicator , battery runtime calculation
Material:	Plastic; aluminum
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 109 cm Width: 7.0 cm Depth: 7.0 cm
Weight:	2.80 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Plastic Case for 4x AKKU IP Pixel Tube 360° CRMX

Maximum load:	50 kg
Case handle:	3 pc/pcs
Lock:	Spring lock: 8 pc/pcs with shut-off function
Transport aid:	Trolley
Material:	Plastic
Color:	Black
Device compartment:	109 cm x 8 cm x 7.5 cm
Middle compartment:	50 cm x 42 cm x 8 cm
Dimensions:	Length: 117.5 cm Depth: 52 cm Height: 21 cm
Weight:	11.40 kg

Scope of delivery:

4 x EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

- 1 x light effect
- 1 x charger
- 1 x power cord
- 1 x remote control
- 1 x battery

1 x stand
2 x fixation clip
2 x splint
1 x user manual
1 x declaration of conformity
1 x adapter

1 x ROADINGER Plastic Case for 4x AKKU IP Pixel Tube 360° CRMX

1 x case