




8X



Features:

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Battery-powered IP pixel tube with RGB/CW/WW color mixing, 360° beam angle and CRMX receiver

- Integrated wireless receiver for CRMX operation
- Cordless, flexible and versatile
- Battery operation up to 8.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 144 LEDs 0.5 W SMD 5050 5in1 RGB/CW/WW (homogenous color mix)
24 segments controlled separately
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend adjustable; color macros preset; white balance adjustable; program selection manual; color animations with two adjustable colors; Emergency lighting function in case of power failure adjustable; Energy-saving mode
- 53 integrated show programs
- Direct color selection for 37 preset colors
- Can be operated in 4; 5; 7; 14; 16; 20.1; 20.2; 22.1; 22.2; 24.1; 24.2; 120; 124 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; CRMX by LumenRadio
- Flicker-free
- With a beam angle of 360°
- Good color rendering index (CRI)
- With holding clip

Logistic

EAN / GTIN: 4026397748154

Weight: 65,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Monochrome OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; rental; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended
- Silent operation
- 3 buttons on the remote control for saving your own settings

ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels

Trunk case with castors

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x castors with 2 locking brakes Ø 100 mm
- 4 x built-in stacking trays in the cover

Technical specifications:

Weight:	63.00 kg
---------	----------

EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

Power supply:	100-240 V AC, 50/60 Hz 13V DC 3000 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC unit (provided) Battery/battery pack
Cable construction:	2 x 0.75 mm² H03VVH2-F
Battery pack type:	1 x lithium ion 10.8 V, 9000 mAh, 97.2 Wh
Battery pack:	Battery operation up to 8.5h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	144 x 0.5 W SMD 5050 5in1 RGB/CW/WW (homogenous color mix)
Flash rate:	2 - 20 Hz
DMX channels:	4; 5; 7; 14; 16; 20.1; 20.2; 22.1; 22.2; 24.1; 24.2; 120; 124
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; CRMX by LumenRadio

Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	12600 Hz
Carrier frequency:	2.4 GHz
Modulation:	GFSK
DMX fail mode:	Hold; blackout; static; full on
Beam angle:	360°
Beam angle (1/2 peak):	360°
Beam angle (1/10 peak):	360°
Color rendering index (CRI):	84 Ra
Housing color:	Black matte
Attachment system:	2x holding clip M10 thread
Display type:	Monochrome OLED display
Display reading:	Charge status indicator , battery runtime calculation
Material:	Plastic; aluminum
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 109 cm Width: 7.0 cm Depth: 7.0 cm
Weight:	2.80 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Cable construction:	3 x 1.5 mm² H07RN-F
Cable length:	1.2 m
Fuse:	5 x 20 mm, 5 A fuse replaceable
Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes Ø 100 mm 4 x built-in stacking trays in the cover
Color:	Black, laminated
Device compartment:	7 cm x 109 cm x 10 cm
Accessory compartment:	113 cm x 9 cm x 21 cm
Material thickness:	9 mm
Dimensions:	Width: 119 cm

Depth: 63 cm
Height: 43.5 cm

Weight: 34.80 kg

Scope of delivery:

8 x EUROLITE AKKU IP Pixel Tube 360° PRO CRMX

1 x light effect
1 x charger
1 x power cord
1 x remote control
1 x battery
1 x stand
2 x fixation clip
2 x splint
1 x user manual
1 x declaration of conformity
1 x adapter

1 x ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and wheels

1 x case
1 x power cord
1 x user manual