



8x



Features:

EUROLITE AKKU Flat Light 3 bk

Flat spotlight with 3 x 8 W RGBW LED, QuickDMX transceiver and bracket

- Integrated QuickDMX transceiver for wireless DMX control
- Elegant housing for indoor use
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- Direct color selection for 30 preset colors
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 12°
- With mounting bracket
- OLED display
- Various versions available
- With a KENSINGTON LOCK theft protection

Logistic

EAN / GTIN: 4026397748376

Weight: 24,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Standing
- Silent operation

ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

Trolley case

- Interior with foam padding
cover with foam padding
- 2 Rugged carrying handles
- 4 high-quality spring locks with shut-off function
- Closes with a
- Trolley

Technical specifications:

Weight:	19.26 kg
---------	----------

EUROLITE AKKU Flat Light 3 bk

Power supply:	100-240 V AC, 50/60 Hz 12.6V DC 2500 mA
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	2 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	3 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; IR remote control; sound to light via microphone
Fixtures available for:	Light´ J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	OLED display

Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 16.8 cm Depth: 13.8 cm Height: 6.2 cm
Weight:	1.62 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

Maximum load:	50 kg
Carrying handle:	2 pc/pcs
Lock:	Spring lock: 4 pc/pcs with shut-off function
Transport aid:	Trolley
Material:	Plastic
Color:	Black
Inside dimensions:	49 cm x 36 cm x 16 cm
Device compartment:	17.8 cm x 6.5 cm x 14 cm
Accessory compartment:	7.8 cm x 32.7 cm x 18.5 cm
Dimensions:	Width: 55 cm Depth: 42 cm Height: 26 cm
Weight:	6.30 kg

Scope of delivery:

8 x EUROLITE AKKU Flat Light 3 bk

1 x spotlight
 1 x user manual
 1 x external mains adapter
 1 x remote control
 1 x battery
 1 x declaration of conformity

1 x ROADINGER Plastic Case for 8x AKKU Flat Light with Trolley

1 x case