

FUTURELIGHT Set 2x DMH-190 Hybrid Moving Head Spot/Beam + Flightcase with wheels

GTIN: 4026397748390



List price: on demand €
incl. 19% VAT.

Features:

FUTURELIGHT DMH-190 Hybrid Moving Head Spot/Beam

PRO spot/beam/wash moving head with 190 W COB LED, zoom, focus, frost and 8 fold prism

- 1 LED 190 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 255° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Exact 16 bit resolution at Dimmer, gobo rotation, zoom, focus
- Color wheel; gobo wheel with static gobos; gobo wheel with rotating gobos; zoom motor driven; focus motor-driven; prism 8-fold; frost filter linear
- Pulse-width modulation adjustable; dimmer curves adjustable; Dimmer speed (step response) adjustable
- Spot effect; beam effect; wash effect
- Color wheel with 10 dichroic filters plus open and CTO correction filter
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 17 gobos and open
shake effect
- Gobo wheel with rotating gobos, 8 gobos and open
gobos changeable
- Shake effect
- Gobo indexable
- Slot-in gobo system for easy gobo replacement
- Rainbow effect with adjustable speed in both directions
- Can be operated in 17; 21 CH mode

Logistic

EAN / GTIN: 4026397748390

Weight: 78,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- The device is cooled by temperature-controlled fan at the base; temperature-controlled fan at the head
- Control via stand-alone; master/slave function; DMX; RDM; sound to light via microphone; CRMX by LumenRadio upgradeable; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 1° - 32°
- With omega bracket
- LCD display,
with battery buffering for easy controlling upgradeable
- 2 Rugged carrying handles
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; stage; theater; wedding/gala/events; rental; video and photography
- Very quiet working noise
- Application possibility: Standing; suspended

ROADINGER Flightcase 2x DMH-190

Trunk case with castors

- With 2 device compartment
- With 1 accessory compartment
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Technical specifications:

Weight:	75.25 kg
---------	----------

FUTURELIGHT DMH-190 Hybrid Moving Head Spot/Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	310 W
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 190 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	255° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 30 Hz

Equipment:	Color wheel; gobo wheel with static gobos; gobo wheel with rotating gobos; zoom motor driven; focus motor-driven; prism 8-fold; frost filter linear
Color generation:	Color wheel with 10 dichroic filters plus open and CTO correction filter Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 17 gobos and open Shake effect Gobo wheel with rotating gobos, 8 gobos and open Outside diameter 13.7mm Image diameter 10mm Gobos changeable Shake effect Gobo indexable Slot-in gobo system for easy gobo replacement Rainbow effect with adjustable speed in both directions
DMX channels:	17; 21
DMX input:	3-pin XLR (M) mounting version IP 5-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP 5-pin XLR (F) mounting version IP
Cooling:	1 x temperature-controlled fan at the base 5 x temperature-controlled fan at the head
Control:	Stand-alone; master/slave function; DMX; RDM; sound to light via microphone; CRMX by LumenRadio upgradeable; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Projection:	Flicker-free
DMX fail mode:	Hold; blackout
Beam angle:	1° - 32°
Beam angle (1/2 peak):	1 - 32°
Beam angle (1/10 peak):	1 - 32°
Color temperature:	6800K
Illuminance in Lux (lx):	Wide cold white (CW) 1m: 28517 lx, 3m: 3875 lx, 6m: 1051 lx
Housing color:	Black
Attachment system:	2x omega bracket
Display type:	LCD display battery buffering upgradeable
USB port:	Type A Type C
Carrying handle:	2 pc/pcs
Transport aid:	4 x rubber feet
Diameter mounting holes:	2 x Ø10mm
Use of brands:	Built with SEETRONIC connector
Material:	Plastic

Dimensions:	Width: 36 cm Depth: 25 cm Height: 53 cm
Weight:	16.30 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Cable construction:	3 x 1.5 mm² H05VV-F

ROADINGER Flightcase 2x DMH-190

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Accessory compartment:	71.5 cm x 10 cm x 30 cm
Device compartment:	35 cm x 37 cm x 53.5 cm
Inside dimensions:	71.5 cm x 49 cm x 53.5 cm
Material thickness:	10 mm
Dimensions:	Width: 78 cm Depth: 54 cm Height: 77 cm
Weight:	38.10 kg

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x XLR cable
- 2 x omega bracket