



List price: 2378.81 €

incl. 19% VAT.

Features:

EUROLITE LED IP PAR 14x10W HCL

Weather-proof (IP65) spotlight with 6in1 RGBWA/UV color mixing and frost filters

- 14 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- Can be operated in 3; 5; 6; 8; 12 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397749359

Weight: 66,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER UG-1 Universal Devicecase

Trunk case with castors

- With 4 device compartments
- Steel ball corner
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes

Technical specifications:

Weight:	62.55 kg
---------	----------

EUROLITE LED IP PAR 14x10W HCL

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	95 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	14 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
Equipment:	Frost filter
DMX channels:	3; 5; 6; 8; 12
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Fixtures available for:	Light´ J; LED PC-Control 512; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´ J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15° 27° 30° 60°
Housing color:	Black matte

Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 31 cm Depth: 22.5 cm Height: 36.5 cm
Weight:	6.80 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 3 mm
Cable construction:	3 x 1.0 mm² H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Material:	Plastic, 2 mm
Dimensions:	Diameter: Ø 20.5 cm
Cable length:	Approx. 1.5 m

ROADINGER UG-1 Universal Devicecase

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	27.5 cm x 27.5 cm x 29 cm
Accessory compartment:	10 cm x 60 cm x 31.5 cm
Dimensions:	Width: 75 cm Depth: 64.5 cm Height: 57 cm
Weight:	28.30 kg

Scope of delivery:

4 x EUROLITE LED IP PAR 14x10W HCL

1 x spotlight
 1 x power cord
 1 x remote control
 3 x frost filter
 1 x XLR cable
 2 x knurled screw
 1 x user manual

1 x ROADINGER UG-1 Universal Devicecase

1 x case