



List price: 1783.81 €

incl. 19% VAT.

Features:

Logistic

EAN / GTIN: 4062397739732

EUROLITE LED Strobe SMD PRO 864 DMX RGB

3in1 LED effect light with RGB color mixing

- 864 LEDs 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
18 segments controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; running light with two adjustable colors
- Strobe effect; wash effect; Blinder effect
- Integrated show programs
- Can be operated in 5; 13; 54 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light
- Flicker-free
- With mounting bracket
- Monochrome LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; restaurants, bars and hotels; rental
- Very quiet working noise
- Application possibility: Suspended

ROADINGER Flightcase 4x LED Strobe SMD PRO

Trunk case with castors

- High-quality workmanship with plywood crosswise glued 9 mm, black
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes Ø 100 mm

Technical specifications:

Weight:	41.71 kg
---------	----------

EUROLITE LED Strobe SMD PRO 864 DMX RGB

Power supply:	230 V AC, 50 Hz
Power consumption:	175 W
Protection class:	Protection class II
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	864 x 0.2 W SMD 5050 3in1 RGB (homogenous color mix)
DMX channels:	5; 13; 54
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle (1/2 peak):	120°
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
Dimensions:	Width: 46.0 cm Depth: 13.5 cm Height: 22.5 cm
Weight:	4.51 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)

ROADINGER Flightcase 4x LED Strobe SMD PRO

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes Ø 100 mm
Material:	Plywood crosswise glued, 9 mm, laminated
Color:	Black
Device compartment:	14 cm x 46.5 cm x 22 cm
Accessory compartment:	11 cm x 48 cm x 22 cm
Dimensions:	Width: 85 cm Depth: 53 cm Height: 49 cm
Weight:	23.67 kg

Scope of delivery:

1 x light effect
1 x power cord
1 x user manual