

FUTURELIGHT Set 2x IP PLH 420 Moving-Head Spot/Beam + Flightcase with wheels

GTIN: 4026397737165



Features:

FUTURELIGHT IP PLH-420 Moving Head Spot/Beam

Weather-proof beam/spot moving head (IP65) with 420 W discharge lamp & CRMX wireless receiver

- Light source: USHIO NSL 421 discharge lamp (2000 hrs)
- Bidirectional rotating 6-fold linear prism and 8-facet prism with variable speed, combinable for multi-facet effects
- Lamp installed and adjusted ex factory
- Positioning within 540° PAN, 265° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 8-fold; prism 6-fold linear; frost filter stepless; zoom motor driven; focus motor-driven
- Scenes user-definable
- Strobe effect
- Color wheel with 13 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 9 gobos and open
shake effect
- Gobo wheel with static gobos, 13 gobos und open
shake effect
- Integrated show programs
- Can be operated in 23 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; RDM; CRMX by LumenRadio; Art-Net; SACN; sound to light via microphone

Logistic

EAN / GTIN: 4026397737165

Weight: 145,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- With a beam angle of 1° - 25° spot
- With bracket with hinged hooks
- Multicolor LCD display,
with battery buffering for easy controlling upgradeable
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; rental
- Application possibility: Standing; suspended

ROADINGER Flightcase 2x IP PLH/PLB 420

Trunk case with castors

- With 2 device compartments
- With 1 accessory compartment
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 chrome tip-over locks
- 6 high-quality butterfly locks with shut-off function
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	140.50 kg
---------	-----------

FUTURELIGHT IP PLH-420 Moving Head Spot/Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	420 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 5 A
Lamp type:	Discharge lamp
Max. TILT movement:	265° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Equipment:	Prism 8-fold; prism 6-fold linear; frost filter stepless; zoom motor driven; focus motor-driven
Color generation:	Color wheel with 13 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 9 gobos and open Outside diameter 15.9mm Image diameter 12mm Shake effect Gobo wheel with static gobos, 13 gobos und open Shake effect

DMX channels:	23
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX; RDM; CRMX by LumenRadio; Art-Net; sACN; sound to light via microphone
Fixtures available for:	Light Captain; GDTF (GrandMA3)
Carrier frequency:	2.4 GHz
Beam angle:	1° - 25° spot
Beam angle (1/2 peak):	Beam 1 - 14° Spot 4 - 25°
Beam angle (1/10 peak):	Spot 4 - 25° Beam 1 - 14°
Housing color:	Black
Attachment system:	2x bracket with hinged hooks
Display type:	Multicolor LCD display battery buffering upgradeable
Connections:	2 x RJ-45 (F) mounting version
Dimensions:	Width: 45 cm Depth: 35 cm Height: 76 cm
Weight:	38.90 kg
Noise classification:	Class 4 (loud noises)

ROADINGER Flightcase 2x IP PLH/PLB 420

Maximum load:	100 kg
Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Stop hinge:	4 pc/pcs
Lock:	Butterfly lock: 6 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Color:	Black, laminated
Accessory compartment:	105 cm x 9 cm x 30 cm
Inside dimensions:	105 cm x 55 cm x 63 cm
Material thickness:	10 mm
Dimensions:	Length: 110 cm Depth: 60.5 cm Height: 89.5 cm
Weight:	51.50 kg

Scope of delivery:

1 x moving light
 1 x user manual
 1 x XLR cable
 1 x power cord
 2 x holder