



List price: 712.81 €

incl. 19% VAT.

Features:

Logistic

EAN / GTIN: 4026397086348

Weight: 12,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE LED PMB-8 COB QCL 30W Bar

LED light effect bar with RGBW color mixing, incl. IR remote control

- 8 LEDs 30 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- Can be operated in 3; 4; 5; 6; 12; 32; 36 CH mode
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 45°
- With mounting bracket
- LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; rental; video and photography; advertisement/Shop window
- Very quiet working noise

- Application possibility: Standing; suspended; on stand

Technical specifications:

Weight:	11.61 kg
---------	----------

EUROLITE LED PMB-8 COB QCL 30W Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 30 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 12; 32; 36
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; Light Captain
Projection:	Flicker-free
Beam angle:	45°
Beam angle (1/2 peak):	45°
Beam angle (1/10 peak):	74°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Material:	Aluminum casting; metal
Dimensions:	Length: 98.0 cm Depth: 16.3 cm Height: 20.6 cm
Weight:	8.65 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm; 3 x Ø10mm; 4 x Ø8mm; 2 x Ø6mm

Material:	Metal, 2.5 mm
Cable construction:	3 x 1.0 mm² H05VV-F
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

EUROLITE Diffuser Cover 15x60° for PMB-8 QCL

Weight:	0.65 kg
---------	---------

EUROLITE Diffuser Cover 25° for PMB-8 QCL

Dimensions:	Length: 98.0 cm
	Width: 12.0 cm
	Depth: 1.5 cm
Weight:	1.05 kg

Scope of delivery:

1 x EUROLITE LED PMB-8 COB QCL 30W Bar

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual

1 x EUROLITE Diffuser Cover 15x60° for PMB-8 QCL

- 1 x beamshaper

1 x EUROLITE Diffuser Cover 25° for PMB-8 QCL

- 1 x beamshaper