



### Features:

#### EUROLITE LED RETRO 6 Spot ABL

Warm white blinder with additional colored LEDs for atmospheric lighting

- 6 LEDs 60 W COB (chip-on-board) amber (A)<BR> LEDs controlled separately
- 108 LEDs 0.1 W SMD 5050 3in1 RGB (homogenous color mix)<BR>12 segments controlled separately
- Blinder effect
- With a beam angle of 120°
- Very quiet working noise
- Flicker-free
- Control via DMX; stand-alone; sound to light; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMx by LumenRadio via USB (optional)
- 3 integrated show programs
- Dimmer electronic
- With mounting bracket
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; restaurants, bars and hotels; rental
- Application possibility: Standing; suspended
- Can be operated in 6; 10; 12; 16; 49 CH mode

### Logistic

EAN / GTIN: 4026397757248

Weight: 16,50 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

## EUROLITE RS-1 Retro Stand

Retro style lighting stand with bag, maximum load 25kg, height 92-155 cm

- The article is delivered pre-assembled
- The article is delivered with practical transport bag
- Adjustable height
- For application areas such as: Wedding/gala/events

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 15.80 kg |
|---------|----------|

## EUROLITE LED RETRO 6 Spot ABL

|                         |                                                                                                                                                              |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                       |
| Power consumption:      | 200 W                                                                                                                                                        |
| Protection class:       | Protection class I                                                                                                                                           |
| Power connection:       | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug                                                                         |
| Cable construction:     | 3 x 1.5 mm² H05VV-F                                                                                                                                          |
| Power output:           | P-Con (grey), mounting version                                                                                                                               |
| Lamp type:              | LED lamp                                                                                                                                                     |
| LED type:               | 6 x 60 W COB (chip-on-board) amber (A)<br>108 x 0.1 W SMD 5050 3in1 RGB (homogenous<br>color mix)                                                            |
| Flash rate:             | 0.8 - 20 Hz                                                                                                                                                  |
| DMX channels:           | 6; 10; 12; 16; 49                                                                                                                                            |
| DMX input:              | 3-pin XLR (M) mounting version<br>5-pin XLR (M) mounting version                                                                                             |
| DMX output:             | 3-pin XLR (F) mounting version<br>5-pin XLR (F) mounting version                                                                                             |
| Cooling:                | 2 x temperature-controlled fan                                                                                                                               |
| Control:                | DMX; stand-alone; sound to light; QuickDMX via<br>USB (optional); W-DMX by wireless solution via<br>USB (optional); CRMX by LumenRadio via USB<br>(optional) |
| Fixtures available for: | Light Captain                                                                                                                                                |
| Projection:             | Flicker-free                                                                                                                                                 |
| PWM frequency:          | 4000 Hz                                                                                                                                                      |
| Beam angle:             | 120°                                                                                                                                                         |
| Beam angle (1/2 peak):  | 120°                                                                                                                                                         |
| Color temperature:      | 1800K                                                                                                                                                        |
| Lamp life:              | 30000 h                                                                                                                                                      |
| Housing color:          | Black                                                                                                                                                        |
| Attachment system:      | Mounting bracket                                                                                                                                             |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                |

|                       |                                                                        |
|-----------------------|------------------------------------------------------------------------|
| USB port:             | Type A                                                                 |
| Use of brands:        | Built with SEETRONIC connector                                         |
| Material:             | Metal                                                                  |
| Dimensions:           | Width: 36 cm<br>Depth: 11 cm<br>Height: 37.5 cm                        |
| Weight:               | 5.00 kg                                                                |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |

**EUROLITE RS-1 Retro Stand**

|                        |                                                             |
|------------------------|-------------------------------------------------------------|
| Maximum load:          | 25 kg                                                       |
| Height:                | Maximum: 155 cm<br>Minimum: 92 cm<br>Adjustable in 12 steps |
| Attachment system:     | Ø 12mm<br>6x M6 thread                                      |
| Type (general stands): | Other stands                                                |
| Material:              | Steel (powder-coated)                                       |
| Color:                 | Black                                                       |
| Transport dimensions:  | 97 cm x 14 cm x 14 cm                                       |
| Base area:             | Ø 120 cm                                                    |
| Mounting size min.:    | 67 cm x 57 cm x 92 cm                                       |
| Mounting size max.:    | 102 cm x 88 cm x 155 cm                                     |
| Weight:                | 9.50 kg                                                     |

**Scope of delivery:**

**1 x EUROLITE LED RETRO 6 Spot ABL**

- 1 x spotlight
- 1 x power cord
- 1 x user manual

**1 x EUROLITE RS-1 Retro Stand**

- 1 x stand
- 1 x bag
- 1 x screw
- 1 x nut