

## ROADINGER Effect rack CO DD, D:25cm, 8U,alu

PRO flightcase for 483 mm devices (19")

Art. No.: 3010721E

GTIN: 4026397326482



### Features:

- Suitable for 483 mm effectors and controllers (19")
- 2 removable covers (double-door version)
- Built-in rack rails
- High-quality workmanship with plywood multilayered glued, aluminum-colored laminated
- Aluminum profile frames (22 mm) with rounded edges
- Three-leg, medium-sized steel ball corners
- 8 spring locks with eyelets for locking-up
- 4 large steel-enforced rubber feet
- 2 hinged, chrome case handles
- Delivery includes mounting screws
- Available in different height units (1 U = 44 mm)
- With profile rails suitable for 19" units
- 8 U
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397326482

Weight: 9,30 kg

Length: 0.55 m

Width: 0.41 m

Height: 0.43 m

### Technical specifications:

|                     |                       |
|---------------------|-----------------------|
| Maximum load:       | 25 kg                 |
| Material thickness: | 7 mm                  |
| Front panel width:  | 19"                   |
| Mounting height:    | Approx. 35.5 cm (8 U) |
| Mounting depth:     | 250 mm                |

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Housing design:                 | 8 U                                             |
| Dimensions:                     | Width: 52.5 cm<br>Depth: 40 cm<br>Height: 42 cm |
| Weight:                         | 8.20 kg                                         |
| Strength:                       | 7 mm                                            |
| Outside dimensions (W x D x H): | 525 x 400 x 420 mm                              |
| Inside dimensions:              |                                                 |
| Mounting width:                 | 483 mm (19")                                    |
| Mounting height:                | 360 mm (4 U)                                    |
| Mounting depth:                 | 250 mm                                          |
| Corner dimensions:              | 36 mm                                           |

**Scope of delivery:**