

## EUROLITE LED PFE-60 WW Profile Spot 20-50°

Profile spotlight, 60 W WW LED, manual zoom, shutter blades, CRI>90

Art. No.: 40001712

GTIN: 4026397715576



### Features:

- 1 LED 60 W COB (chip-on-board) warm white (WW)
- Zoom manual; focus manual
- Very high color rendering index (CRI)
- Flicker-free
- Very quiet working noise
- Control via stand-alone; master/slave function; DMX; RDM
- Dimmer electronic; pulse-width modulation variable
- Strobe effect
- With mounting bracket
- Multicolor OLED display
- The device is cooled by temperature-controlled fan
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; rental; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 1; 2 CH mode
- With a beam angle of 20° - 50°

### Logistic

EAN / GTIN: 4026397715576

Weight: 3,77 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.22 m

### Technical specifications:

|                    |                                          |
|--------------------|------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                   |
| Power consumption: | 60 W                                     |
| Protection class:  | Protection class I                       |
| Power connection:  | Fixed power supply cord with safety plug |

|                                  |                                                                        |
|----------------------------------|------------------------------------------------------------------------|
| Fuse:                            | T 1 A fuse replaceable                                                 |
| Lamp type:                       | LED lamp                                                               |
| LED type:                        | 1 x 60 W COB (chip-on-board) warm white (WW)                           |
| Equipment:                       | Zoom manual; focus manual                                              |
| DMX channels:                    | 1; 2                                                                   |
| DMX input:                       | 3-pin XLR (M) mounting version                                         |
| DMX output:                      | 3-pin XLR (F) mounting version                                         |
| Cooling:                         | Temperature-controlled fan                                             |
| Control:                         | Stand-alone; master/slave function; DMX; RDM                           |
| Fixtures available for:          | Light Captain                                                          |
| Projection:                      | Flicker-free                                                           |
| Beam angle:                      | 20° - 50°                                                              |
| Beam angle (1/2 peak):           | 20 - 50°                                                               |
| Beam angle (1/10 peak):          | 20 - 50°                                                               |
| Color temperature:               | 3200K                                                                  |
| Color rendering index (CRI):     | 94 Ra                                                                  |
| Lamp life:                       | 50000 h                                                                |
| Luminous flux:                   | 4500 lm                                                                |
| Housing color:                   | Black matte                                                            |
| Attachment system:               | Mounting bracket                                                       |
| Display type:                    | Multicolor OLED display                                                |
| Material:                        | Aluminum casting; metal                                                |
| Dimensions:                      | Length: 35.0 cm<br>Width: 16.0 cm<br>Height: 25.5 cm                   |
| Weight:                          | 3.20 kg                                                                |
| Noise classification:            | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Energy efficiency class (A - G): | F                                                                      |
| EPREL-Nr:                        | 1597557                                                                |
| Diameter mounting holes:         | 1 x Ø12mm                                                              |
| Material:                        | Metal, 3 mm                                                            |
| Gobos:                           | Outside diameter 37mm<br>Image diameter 25mm                           |
| Material:                        | Aluminum, 0.5 mm; plastic                                              |
| Dimensions:                      | Diameter: Ø 3 cm                                                       |

### Scope of delivery:

1 x spotlight  
1 x gobo holder  
1 x user manual