EUROLITE LED Mini PFE-12 CW

Art. No.: 40001762

Fanless spotlight with 12 W COB LED, adjustable light beam shape, color rendering index (CRI) >90

GTIN: 4026397742114











Features:

- 4 shutter blades
- With a beam angle of 28°
- 1 LED COB (chip-on-board) cold white (CW)
- Focus manual
- Very high color rendering index (CRI)
- Very quiet working noise
- With mounting bracket
- Spot effect
- The device is cooled by passive convection cooling
- Various versions available
- Easy installation
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Application possibility: Standing; suspended
  knurled screw
- M4 thread

Logistic

EAN / GTIN: 4026397742114
Weight: 0,67 kg
Length: 0.24 m
Width: 0.20 m
Heigth: 0.14 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	12 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable construction:	3 x 0.75 mm² H05VV-F
Lamp type:	LED lamp
LED type:	1 x COB (chip-on-board) cold white (CW)
Equipment:	Focus manual
Cooling:	Passive convection cooling
Setup:	Easy installation
Beam angle:	28°
Beam angle (1/2 peak):	28°
Color temperature:	5800K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	1m: 2103 lx, 3m: 231 lx, 6m: 91 lx
Luminous flux:	1080 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Length: 19 cm Width: 8.5 cm Height: 12.5 cm
Weight:	0.50 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	G
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 1 mm
Thread:	M4 thread x 16 mm

Scope of delivery:

1 x device
1 x key
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.