

EUROLITE LED PPC-20 WW Spot

Fanless spotlight with 20 W COB LED, adjustable beam angle, color rendering index (CRI) >95

Art. No.: 40001775

GTIN: 4026397701364



Features:

- Four beam angles adjustable via lens settings within the housing
- With plano-convex lens
- With a beam angle of 10°
- Silent operation
- Very high color rendering index (CRI)
- Flicker-free
- 1 LED 20 W COB (chip-on-board) warm white (WW)
- Control via rotary dial for brightness
- The device is cooled by passive convection cooling
- For application areas such as: Decoration; Trade fair and shop fitting; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397701364

Weight: 1,32 kg

Length: 0.25 m

Width: 0.14 m

Height: 0.15 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
Protection class:	Protection class I
Power connection:	Mains input via 3-pin screw plug connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable

Lamp type:	LED lamp
LED type:	1 x 20 W COB (chip-on-board) warm white (WW)
Cooling:	Passive convection cooling
Control:	Rotary dial for brightness
Projection:	Flicker-free
Beam angle:	10°
Beam angle (1/2 peak):	10°
	15°
	18°
	22°
Beam angle (1/10 peak):	19°
	27°
	30°
	34°
Color temperature:	3000K
Color rendering index (CRI):	97 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 1m: 6073 lx, 3m: 742 lx, 6m: 194 lx
	Wide warm white (WW) 1m: 2718 lx, 3m: 350 lx, 6m: 92 lx
Housing color:	Black
Dimensions:	Length: 19.5 cm
	Width: 11.5 cm
	Height: 16.5 cm
Weight:	1.12 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x mounting bracket
- 1 x screw