

EUROLITE LED PFR-50 WW Fresnel Spot

Compact spotlight with 20 W COB LED, manual zoom, color rendering index (CRI) >95

Art. No.: 40001790

GTIN: 4026397703740



List price: 343.91 €

incl. 19% VAT.

Features:

- With fresnel lens
- 1 LED 20 W COB (chip-on-board) warm white (WW)
- Very high color rendering index (CRI)
- Very quiet working noise
- Flicker-free
- Control via stand-alone; DMX (optional); master/slave function (optional)
- The device is cooled by cooling fan
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; video and photography
- Application possibility: Suspended; on stand
- With a beam angle of 11° - 40°

Logistic

EAN / GTIN: 4026397703740

Weight: 2,35 kg

Length: 0.39 m

Width: 0.20 m

Height: 0.20 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	48 W
Protection class:	Protection class I
Power connection:	Mains input via 3-pin screw plug connector (M) mounting version power supply cord with safety plug (provided)
Power output:	3-pin screw plug connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable

Lamp type:	LED lamp
LED type:	1 x 20 W COB (chip-on-board) warm white (WW)
Cooling:	Cooling fan
Control:	Stand-alone; DMX (optional); master/slave function (optional)
Projection:	Flicker-free
Beam angle:	11° - 40°
Beam angle (1/2 peak):	11 - 30°
Beam angle (1/10 peak):	21 - 40°
Color temperature:	3100K
Color rendering index (CRI):	96 Ra
Illuminance in Lux (lx):	Narrow warm white (WW) 1m: 20302 lx, 3m: 2529 lx, 6m: 667 lx Wide warm white (WW) 1m: 5751 lx, 3m: 748 lx, 6m: 207 lx
Housing color:	Black
Material:	Plastic; aluminum
Slot for spot length:	Ø 11 cm
Dimensions:	Length: 30.5 cm Width: 16.0 cm Height: 22.0 cm
Weight:	1.94 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Diameter mounting holes:	1 x Ø11mm; 2 x Ø8mm; 4 x Ø4mm
Material:	Aluminum, 3 mm
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.4 m
Material:	Metal, 1 mm
Ring diameter:	Outside: 99 mm Inside: 90 mm

Scope of delivery:

1 x spotlight
 1 x power cord
 1 x barndoor
 1 x plug (male)
 1 x user manual