

EUROLITE LED PFE-50 3000K Profile Spot

Handy stage spotlight with 50 W COB LED in modular construction system, CRI >80

Art. No.: 40001800

GTIN: 4026397579284



Features:

- Modular construction kit that can be customized to individual preferences
- 4 shutter blades
- Dimmer and strobe, master/slave functions adjustable via optional DMX interface
- Dimmable
- 1 LED 50 W COB (chip-on-board) warm white (WW)
- The device is cooled by cooling fan
- Control via on/off switch on device; master/slave function
- Flicker-free
- With a beam angle of 19°
- Very high color rendering index (CRI)
- With mounting bracket
- Very quiet working noise
- For application areas such as: Trade fair and shop fitting; installation; theater; rental
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397579284  
Weight: 2,45 kg  
Length: 0.38 m  
Width: 0.20 m  
Heigh: 0.20 m

Technical specifications:

|                    |                                                                                                    |
|--------------------|----------------------------------------------------------------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                                                                             |
| Power consumption: | 55 W                                                                                               |
| Power connection:  | Mains input via 3-pin screw plug connector (M) IP<br>power supply cord with safety plug (provided) |
| Power output:      | 1 x 3-pin screw plug connector (F) IP                                                              |
| Lamp type:         | LED lamp                                                                                           |

|                              |                                                                        |
|------------------------------|------------------------------------------------------------------------|
| Lamp specification:          | Dimmable                                                               |
| LED type:                    | 1 x 50 W COB (chip-on-board) warm white (WW)                           |
| Cooling:                     | Cooling fan                                                            |
| Control:                     | On/off switch on device; master/slave function                         |
| Fixtures available for:      | LED PC-Control 512; Light Captain; Light´J                             |
| Projection:                  | Flicker-free                                                           |
| Beam angle:                  | 19°                                                                    |
| Beam angle (1/2 peak):       | 19° (optional)<br>26° (optional)<br>36° (optional)<br>50° (optional)   |
| Color temperature:           | 3000K                                                                  |
| Color rendering index (CRI): | 91 Ra                                                                  |
| Illuminance in Lux (lx):     | Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx                      |
| Housing color:               | Black                                                                  |
| Attachment system:           | Mounting bracket                                                       |
| Dimensions:                  | Length: 30.5 cm<br>Width: 13.4 cm<br>Height: 23.8 cm                   |
| Weight:                      | 1.97 kg                                                                |
| Noise classification:        | Class 1 (very slight noise, suitable for noise-sensitive environments) |

**Scope of delivery:**

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x filter frame
- 1 x gobo holder
- 1 x terminating plug (power)