

EUROLITE AKKU PLL-168 WW/CW Panel

Battery-powered surface light with 168 dual white LEDs, QuickDMX port and barn doors

Art. No.: 40001845

GTIN: 4026397703016



Features:

- 4 barn doors to avoid blinding the audience and for protection during transport
- Slim, rugged metal housing
- Cordless, flexible and versatile
- Battery operation up to 8h depending on program used
- With a beam angle of 120°
- Very high color rendering index (CRI)
- Variable color temperature 2800 K - 6500 K
- Silent operation
- Flicker-free
- Control via stand-alone; sound to light via microphone; master/slave function; DMX; rotary dial for brightness and color temperature; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Dimmer electronic; pulse-width modulation variable; Energy-saving mode
- Integrated show programs
- Direct color selection for 38 preset colors
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Decoration; theater; video and photography; stage
- Application possibility: Suspended; on stand
- Can be operated in 2; 4; 6 CH mode

Logistic

EAN / GTIN: 4026397703016

Weight: 3,90 kg

Length: 0.40 m

Width: 0.25 m

Height: 0.15 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Battery pack type:	1 x lithium ion 22.2 V, 4400 mAh, 97.68 Wh
Battery pack:	Battery operation up to 8h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	84 x 0.5 W SMD 2835 cold white (CW) 84 x 0.5 W SMD 2835 warm white (WW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; sound to light via microphone; master/slave function; DMX; rotary dial for brightness and color temperature; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	2800K - 6500K adjustable
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 35.7 cm Depth: 11.7 cm Height: 22.0 cm
Weight:	3.60 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord