

EUROLITE LED PLL-360 6000K Panel

Surface light with 360 cold white (CW)LEDs and DMX

Art. No.: 40001891

GTIN: 4026397616835



Features:

- 4 barn doors to avoid blinding the audience and for protection during transport
- Frost filter provides a soft, homogeneous light
- Very high color rendering index (CRI)
- With a beam angle of 120°
- Silent operation
- Flicker-free
- Dimmable
- Slim, rugged metal housing
- Control via quick select potentiometer for brightness; DMX; master/slave function
- Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- With mounting bracket
- Rugged carrying handle
- Mains input and output for power linking up to 8 units
- Various versions available
- Energy-saving, durable and environmentally friendly
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 3 CH mode

Logistic

EAN / GTIN: 4026397616835

Weight: 6,90 kg

Length: 0.63 m

Width: 0.15 m

Height: 0.37 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	130 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED type:	360 x 0.5 W SMD 2835 cold white (CW)
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Quick select potentiometer for brightness; DMX; master/slave function
Fixtures available for:	Light´ J; LED PC-Control 512; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	6000K
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 498 lx, 6m: 148 lx
Lamp life:	50000 h
Luminous flux:	9937 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Carrying handle:	1 pc/pcs
Dimensions:	Width: 57 cm Depth: 12 cm Height: 31 cm
Weight:	6.10 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	1056097

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord