

EUROLITE LED PLL-384 CW/WW Panel

DMX-controlled surface light with 384 dual white LEDs, QuickDMX port, frost filter and barn doors

Art. No.: 40001892

GTIN: 4026397698541



Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- With a beam angle of 120°
- Very high color rendering index (CRI)
- Variable color temperature 2700 K - 5700 K
- Direct color temperature selection for 69 preset values
- Very quiet working noise
- Flicker-free
- Control via rotary dial for brightness and color temperature; DMX; master/slave function; stand-alone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- With mounting bracket
- Energy-saving, durable and environmentally friendly
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 2-1; 2-2; 3-1; 3-2; 4 CH mode

Logistic

EAN / GTIN: 4026397698541

Weight: 3,90 kg

Length: 0.37 m

Width: 0.19 m

Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 100 W

Protection class: Protection class I

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (grey), mounting version
Fuse:	T 3.15 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	192 x 0.5 W SMD 5730 cold white (CW) 192 x 0.5 W SMD 5730 warm white (WW)
Flash rate:	1 - 28 Hz
DMX channels:	2-1; 2-2; 3-1; 3-2; 4
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Rotary dial for brightness and color temperature; DMX; master/slave function; stand-alone; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	4200 Hz
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	2700K - 5700K adjustable
Color rendering index (CRI):	94 Ra
Illuminance in Lux (lx):	Wide cold white (CW) 1m: 2324 lx, 3m: 276 lx, 6m: 83 lx Wide warm white (WW) 1m: 2277 lx, 3m: 249 lx, 6m: 76 lx Wide all 1m: 3530 lx, 3m: 407 lx, 6m: 124 lx Narrow cold white (CW) 1m: 2789 lx, 3m: 327 lx, 6m: 98 lx Narrow warm white (WW) 1m: 2542 lx, 3m: 297 lx, 6m: 94 lx Narrow all 1m: 4167 lx, 3m: 508 lx, 6m: 150 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Metal
Dimensions:	Length: 34.7 cm Width: 13.8 cm Height: 21.1 cm
Weight:	3.52 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Diameter mounting holes:	1 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm
Material:	Metal, 2 mm
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.2 m

Scope of delivery:

1 x spotlight
1 x power cord
1 x frost filter
2 x knurled screw
1 x user manual