

EUROLITE LED PFE-120 3000K Profile Spot

PRO profile spotlight, 120 W warm white LED, zoom, shutter blades

Art. No.: 40001981

GTIN: 4026397557008



The article is no longer in our assortment.

Features:

- Professional stage spot light
- Stand-alone or DMX mode
- Control panel with LC display for easy configuration
- Master/slave function
- Strobe effect 0-20 Hz
- Electronic dimmer (0-100%)
- Dimmer speed (step response) adjustable
- Focus manually adjustable
- Manually adjustable zoom 14-41°
- Color filter frame and 4 shutter blades included in delivery
- Swivel mounting bracket
- Mains input and output for power linking up to 8 units
- 1 LED 120 W COB (chip-on-board) warm white (WW)
- Can be operated in 3 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX
- With a beam angle of 14° - 41°
- LCD display

Logistic

EAN / GTIN: 4026397557008

Weight: 12,85 kg

Length: 0.74 m

Width: 0.36 m

Height: 0.34 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 120 W

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) warm white (WW)
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Beam angle:	14° - 41°
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Color temperature:	3000K
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 61.5 cm Width: 28 cm Height: 42 cm
Weight:	11.10 kg
Noise classification:	Class 2 (slight noise)

Scope of delivery:

1 x spotlight
 1 x filter frame
 1 x power cord
 1 x user manual
 1 x plug (male)